INTRODUCING THE NEW PATRICT PAT75013



T3 TECHNOLOGY WITH ONBOARD GPS

Record when and where crimps occur, unassisted by external devices.

- Onboard GPS maps crimp locations
- Bluetooth[®] enabled for instant crimp data
- Remotely observe project status
- Output force validation, green/red LED
- Flag & enter comments for individual crimps
- Manage BURNDY[®] T3 tool inventory
- Link accounts and securely share tools
- Sync and upload data to the cloud
- Create custom reports for projects

All of the exceptional features of its PATRIOT predecessor, plus a new ergonomic design and state of the art technology.

TRACK: Map location of crimps

RNDY 750 T3





Connecting Power to Your World[®]



PATRIOT[®] 12 Ton with T3 Technology TRACK | TRACE | TRANSMIT

Tool Series: PAT750T3

- TRACK crimp locations with onboard GPS BURNDY Exclusive! •
- **TRACE** individual crimps with comments and output force validation •
- TRANSMIT via Bluetooth[®] technology and sync data to the cloud ٠
- C-head with 1.65" jaw opening and 355° head rotation •
- Used with U dies •
- Patented T-Track alignment guide for HYGROUND® as well as other asymmetrical connectors
- Bright LED Worklight and Red/Green LED to validate output force
- Improved ergonomic design with more balance and better grip to reduce user fatigue

For Use On:

Tension Sleeves

	63
Copper	#8 sol 500 k
Aluminum	#8 sol 587.2
ACSR	#4 - 556.5 kcr
Taps	

kcmil 2 kcmil mil

1 Copper

#14 sol. - 500 kcmil Aluminum #8 - 500 kcmil

#6 - 500 kcmil

Aerial Cable

Copper

Terminals & Splices #8 - 750 kcmil Copper Aluminum #8 - 750 kcmil ACSR #4 - 556.5 kcmil

HYGROUND[®] (Compression Grounding)

#8 - 500 kcmil Copper Ground Rods 1/2" - 1" diameter

Variations:

PAT750T3U03A2	
PAT750T3C03A2	
PAT750T3U05A2	
PAT750T3C05A2	

with 3.0Ah Li-Ion batteries with rubber covered head (3.0Ah) with 5.0Ah Li-lon batteries with rubber covered head (5.0Ah)

PAT750T3U03A3 with 3.0Ah Li-Ion batteries, pro bag with rubber covered head (3.0Ah), pro bag PAT750T3C03A3 PAT750T3U05A3 with 5.0Ah Li-lon batteries, pro bag PAT750T3C05A3 with rubber covered head (5.0Ah), pro bag



Specifications:

Output Force:	12 Tons
Tool Weight:	16.1 lbs
Size:	15.75" x 14.75" x 3.25"
Die Style:	U style
Jaw Opening:	1.65"
Operating Voltage:	18 V-DC Lithium-Ion (Accepts 2.0Ah-6.0Ah Makita)
Recharge Time:	30 minutes (3.0Ah) 45 minutes (5.0Ah)
Warranty:	5 year limited warranty Lifetime warranty on INFINITY DRIVE [®] 3 year on batteries and charger
Kits Include:	2 batteries, charger, lanyard, and carrying case

Accessories:

BAT18VLI:	3.0Ah Li-lon battery
BAT18V5AHLI:	5.0Ah Li-lon battery
PATCHGRLI:	120V-AC Charger
PATCHGRLIDC:	12/24V-DC Charger
PT208620:	Lanyard
FORCEGAUGE1215:	Force Test Gauge

See Important Notes page at start of Catalog. Technical Service 1-800-451-4956 **Tool Service Center 1-800-426-8720**

Customer Service 1-800-387-6487 | Quebec 1-800-361-6975 | www.burndy.com



Connecting Power to Your World[®]



© BURNDY LLC 2019