

UL 98 Fused Rotary Disconnect Switches—200 & 400A

Standard Class J

For a Complete Assembly, Please Select:

SWITCH + LUGS		Switch										
		Amp Rating	Fuse Class	Number of Poles	SCCR	Max Horsepower Rating				DC*		Part Number
						1-Phase 220/240Vac	220/240Vac	440/480Vac	600 Vac	125 Vdc	250 Vdc	
		200	J	2	200kA	10	-	-	-	-	-	RDF200J-2
		200	J	3	200kA	-	60	125	150	-	-	RDF200J-3
		200	J	4	200kA	-	60	125	150	-	-	RDF200J-4
		400	J	2	200kA	10	-	-	-	20	50	RDF400J-2
		400	J	3	200kA	-	125	250	350	20	50	RDF400J-3
		400	J	4	200kA	-	125	250	350	20	50	RDF400J-4
		* DC Ratings use two poles in series.										
Terminal Lug Kit		Terminal Lug Kit										
		Switch Amp Rating	Number of Poles	Lugs Per Kit	Wire Range			Wire Type		Part Number		
					200	200	200	400	400		400	
		200	2	2	#6-300MCM			75°C Cu/Al		LUG1-2		
		200	3	3	#6-300MCM			75°C Cu/Al		LUG1-3		
		200	4	4	#6-300MCM			75°C Cu/Al		LUG1-4		
		400	2	2	#4-600MCM or Dual 1/0-250MCM			75°C Cu/Al		LUG2-2		
400	3	3	#4-600MCM or Dual 1/0-250MCM			75°C Cu/Al		LUG2-3				
400	4	4	#4-600MCM or Dual 1/0-250MCM			75°C Cu/Al		LUG2-4				
Direct Mount Handle		Direct Mount Handle - mounts directly to switch, no shaft required										
		For Switch Part Number	Color	Test Function	Padlockable						Part Number	
		All Switches	Black	Y	Y						DIR-07	
Select for Standard Applications	 or  + 	External Front Operated Pistol Handles - shaft required										
		NEMA Type	Color	Test Function	Padlockable	Defeatable					Part Number	
		1, 3R, 12	Black	N	Y	Y					H12-03B	
		1, 3R, 12	Red/Yellow	N	Y	Y					H12-03R	
		1, 3R, 4, 4X, 12	Black	N	Y	Y					H4X-06B	
		1, 3R, 4, 4X, 12	Red/Yellow	N	Y	Y					H4X-06R	
		1, 3R, 4, 4X, 12	Black	Y	Y	Y					H4X-06TB	
		1, 3R, 4, 4X, 12	Red/Yellow	Y	Y	Y					H4X-06TR	
		Metallic Hasp (Heavy Duty) External Front Operated Pistol Handles - shaft required										
		NEMA Type	Color	Test Function	Padlockable	Defeatable					Part Number	
		1, 3R, 4, 4X, 12	Black	N	Y	Y					H4X-06BHD	
		1, 3R, 4, 4X, 12	Red/Yellow	N	Y	Y					H4X-06RHD	
		External Right Side Operated Pistol Handles - shaft required										
		NEMA Type	Color	Test Function	Padlockable	Defeatable					Part Number	
		1, 3R, 4, 4X, 12	Black	N	Y	N/A					H4X-06SB	
		1, 3R, 4, 4X, 12	Red/Yellow	N	Y	N/A					H4X-06SR	
		Shafts for Pistol Handles										
		Length in (mm)	Mounting Depth (X) in (mm)								Part Number	
		7.9 (200)	200A: 5.70-9.06 (145-230) 400A: 7.87-10.24 (200-260)								SH5-200	
		12.6 (320)	200A: 5.70-13.78 (145-350) 400A: 7.87-16.93 (200-380)								SH5-320	
15.7 (400)	200A: 5.70-16.93 (145-430) 400A: 7.87-18.10 (200-460)		SH5-400									