









Modular Terminal Blocks

Feed-through and Earth terminals









Type
 <p>ZDK 2.5/1.5</p> 
 <p>ZDK 2.5/1.5 V</p> 
 <p>ZDK 2.5/1.5 DU PE</p> 
 <p>ZDK 2.5/1.5 PE</p> 

Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Width (mm)	Colour	Qty.	End Plates and Partitions
1674300000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Beige	50	1674730000
1678630000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Blue	50	1748800000
1689990000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Beige	50	1674730000
1745880000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Blue	50	1748800000
1689970000	0.5 ... 2.5	0.5 ... 2.5	-	20 A	5.1	Beige	50	1674730000
1690000000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Green	50	1674730000

Note: Qty. above is recommended pack sizes

Multi-tier terminals

Type
 <p>ZLD 2.5-2 N</p> 
 <p>ZLD 2.5-2 VN</p> 
 <p>ZMAK 2.5</p> 
 <p>ZVLD 2.5</p> 









Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Width (mm)	Colour	Qty.	End Plates and Partitions
1782300000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Beige	50	1782340000
1782310000	0.5 ... 2.5	0.5 ... 2.5	500 V	20 A	5.1	Blue	50	1782350000
1782320000	0.5 ... 2.5	0.5 ... 2.5	400 V	20 A	5.1	Beige	25	1782340000
1782330000	0.5 ... 2.5	0.5 ... 2.5	400 V	20 A	5.1	Blue	25	1782350000
1768000000	0.5 ... 2.5	0.5 ... 2.5	400 V	24 A	5.1	Beige	25	1768010000
1208920000	0.5 ... 2.5	0.5 ... 2.5	250 V	20 A	5.1	Beige	50	1210410000

Note: Qty. above is recommended pack sizes

Modular Terminal Blocks

Disconnect terminals











Type
 <p>ZTR 2.5</p> <p>Without disconnecter</p> 
 <p>ZTR 2.5/3AN</p> <p>Without disconnecter</p> 
 <p>ZTR 2.5/4AN</p> <p>Without disconnecter</p> 
 <p>ZDTR 2.5</p> 

Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Width (mm)	Colour	Qty.	End Plates and Partitions
1831280000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Beige	100	1608740000
8731710000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Blue	100	1608740000
1831130000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Beige	100	1608740000
8731720000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Beige	100	1608800000
8731730000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Blue	100	1608800000
8728450000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	Beige	100	1608800000
7920900000	0.5 ... 2.5	0.5 ... 1.5	400 V	16 A	5.1	Beige	100	1608800000
7920930000	0.5 ... 2.5	0.5 ... 1.5	400 V	16 A	5.1	Blue	100	1608800000
7920950000	0.5 ... 2.5	0.5 ... 1.5	400 V	16 A	5.1	Beige	100	1608800000
1745400000	0.5 ... 4.0	0.5 ... 2.5	400 V	16 A	5.1	Beige	20	1745420000
1798330000	0.5 ... 4.0	0.5 ... 2.5	400 V	16 A	5.1	Blue	20	1745420000

Note: Qty. above is recommended pack sizes

Fuse terminals

Type
 <p>ZSI 2.5/5x20</p> <p>400 V AC/DC 10-36 V AC/DC with LED 30-70 V AC/DC with LED 60-150 V AC/DC with LED 140-250 V AC/DC with LED</p> 
 <p>ZSI 2.5/5x25</p> <p>400 V AC/DC</p> 
 <p>ZSI 2.5/2</p> <p>400 V AC/DC 10-36 V AC/DC with LED 30-70 V AC/DC with LED 60-150 V AC/DC with LED 140-250 V AC/DC with LED</p> 
 <p>ZTR 2.5/2*</p> <p>400 V AC/DC</p> 
 <p>ZTR 2.5/4 AN*</p> <p>400 V AC/DC</p> 

Note: *With fuse SIHA

Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Colour	Qty.	End Plates and Partitions
1616400000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1616440000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1616430000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1616420000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1616410000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1730900000	0.5 ... 4.0	0.5 ... 2.5	500 V	6.3 A	7.9	50	1608800000
1616460000	0.5 ... 4.0	0.5 ... 2.5	500 V	12 A	7.9	10	-
1616470000	0.5 ... 4.0	0.5 ... 2.5	500 V	12 A	7.9	10	-
1616480000	0.5 ... 4.0	0.5 ... 2.5	500 V	12 A	7.9	10	-
1616490000	0.5 ... 4.0	0.5 ... 2.5	500 V	12 A	7.9	10	-
1616500000	0.5 ... 4.0	0.5 ... 2.5	500 V	12 A	7.9	10	-
1831130000	0.5 ... 4.0	0.5 ... 2.5	500 V	20 A	5.1	100	1608740000
7920950000	0.5 ... 2.5	0.5 ... 1.5	400 V	16 A	5.1	100	1608800000

Note: Qty. above is recommended pack sizes

End bracket









Type
 <p>ZEW 35</p>

Technical data / Ordering data

Order No.	Qty.
9540000000	20

Note: Qty. above is recommended pack sizes

Double level feed-through and twin connection

Type
 <p>WDU 1.5ZZ</p>
 <p>WDU 2.5/1.5/ZR</p>
 <p>WDK 2.5/ZQV</p>
 <p>WDK 2.5</p>
 <p>WDK 2.5N</p>
 <p>WDK 2.5N V</p>
 <p>WDK 4N</p>
 <p>WDK 4N V</p>



Note: ZQV = pluggable cross connectors, an innovation of Weidmüller

Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Width (mm)	Colour	Qty.	End Plates and Partitions
1031400000	0.5 ... 1.5	0.5 ... 1.5	800 V	17.5 A	5.1	Beige	100	1050000000
1031480000	0.5 ... 1.5	0.5 ... 1.5	800 V	17.5 A	5.1	Blue	100	1050080000
1024700000	0.5 ... 4.0	0.5 ... 2.5	800 V	17.5 A	5.1	Beige	100	1050000000
1024780000	0.5 ... 4.0	0.5 ... 2.5	800 V	17.5 A	5.1	Blue	100	1050080000
1041100000	0.5 ... 4.0	0.5 ... 2.5	400 V	24 A	5.1	Beige	100	1059100000
1041180000	0.5 ... 4.0	0.5 ... 2.5	400 V	24 A	5.1	Blue	100	1059180000
1021500000	0.5 ... 4.0	0.5 ... 2.5	400 V	24 A	5.1	Beige	100	1059100000
1021580000	0.5 ... 4.0	0.5 ... 2.5	400 V	24 A	5.1	Blue	100	1059180000
1041600000	0.5 ... 4.0	0.5 ... 2.5	800 V	24 A	5.1	Beige	100	1084000000
1041680000	0.5 ... 4.0	0.5 ... 2.5	800 V	24 A	5.1	Blue	100	1084080000
1041610000	0.5 ... 4.0	0.5 ... 2.5	800 V	24 A	5.1	Beige	100	1084000000
1041900000	0.5 ... 6	0.5 ... 4	800 V	32 A	6.1	Beige	100	1084000000
1041980000	0.5 ... 6	0.5 ... 4	800 V	32 A	6.1	Blue	100	1084080000
1041910000	0.5 ... 6	0.5 ... 4	800 V	32 A	6.1	Beige	100	1084000000

Note: Qty. above is recommended pack sizes

Feed-through and earth terminals

Type
 <p>WPE 1.5/ZZ</p>
 <p>WPE 2.5/1.51 ZR</p>

Technical data / Ordering data

Order No.	Solid/Stranded Rated Connection (mm ²)	Flexible/Ferrule Rated Connection (mm ²)	Rated voltage	Rated current	Width (mm)	Colour	Qty.	End Plates and Partitions
1016500000	1.5 ... 2.5	0.5 ... 1.5	800 V	-	5.1	Green/ Yellow	100	1050000000
1016400000	1.5 ... 4.0	0.5 ... 2.5	800 V	-	5.1	Green/ Yellow	100	1050000000

Note: Qty. above is recommended pack sizes