


GFCIs

Self-Test GFCI Receptacles 2 Pole, 3 Wire Grounding 15 & 20A, 125VAC



1596TRLA


Features

- Self-Test GFCI with SafeLock™ Protection – conducts an automatic test every second, ensuring it's always ready to protect. If critical components are damaged and protection is lost, power to the receptacle will be locked out.
- Protects children: patented shutter system helps prevent improper insertion of foreign objects.
- Meets National Electrical Code® Tamper-Resistant requirements.
- Prevents line-load reversal miswire: no power to the face or downstream receptacles if wire incorrectly.
- Exceeds UL943 voltage surge requirements; survives 100x the required UL 3kA/6kV voltage surge test cycles.
- FSUL Listed (Federal Specification WC596).
- Auto-ground clip assures a positive ground to metal box.
- Trip indicator light (red LED).
- Side or internal screw-pressure-plate back wire with #10 – #14 AWG solid or stranded copper wire.
- Two back wire holes per terminal.
- Ground screw has a back wire clamp for easy installation.
- 10kA short circuit rating.
- Mounting screws are shipped captive in the device and wall plate for easier installation.
- High-impact-resistant thermoplastic construction.
- Extra-long strap.
- Button colors match the device face.
- Dual-direction test and reset buttons.
- Supplied with matching TP26 nylon wall plate (except NI, TI, AB, and DB models).
- Tri-drive screws.

Specifications

- Supply Voltage: 125VAC, 60 Hz
- Supply Voltage Range: 102-132 VAC
- Trio Threshold: 5± 1mA
- Trip Time: 0.025 sec., nominal per UL Standard
- 20 Amp feed-thru capacity

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	VAC			UL943	UL498	FSUL WC596
TRADEMASTER TAMPER-RESISTANT DUPLEX							
1596TRI	15	125	Ivory	5-15R	•	•	•
1596TRW	15	125	White	5-15R	•	•	•
1596TRLA	15	125	Light Almond	5-15R	•	•	•
SPEC GRADE TAMPER-RESISTANT DUPLEX							
2096TRI	20	125	Ivory	5-20R	•	•	•
2096TRW	20	125	White	5-20R	•	•	•
2096TRLA	20	125	Light Almond	5-20R	•	•	•
SPEC GRADE DUPLEX							
2096I	20	125	Ivory	5-20R	•	•	•
2096W	20	125	White	5-20R	•	•	•
2096	20	125	Brown	5-20R	•	•	•
2096GRY	20	125	Gray	5-20R	•	•	•
2096LA	20	125	Light Almond	5-20R	•	•	•
HOSPITAL GRADE DUPLEX							
2096HGI	20	125	Ivory	5-20R	•	•	•
2096HGW	20	125	White	5-20R	•	•	•
2096HG	20	125	Brown	5-20R	•	•	•
2096HGGRY	20	125	Gray	5-20R	•	•	•
2096HGRED	20	125	Red	5-20R	•	•	•
2096HGLA	20	125	Light Almond	5-20R	•	•	•
HOSPITAL GRADE TAMPER-RESISTANT DUPLEX							
2096HGTRI	20	125	Ivory	5-20R	•	•	•
2096HGTRW	20	125	White	5-20R	•	•	•
2096HGTRLA	20	125	Light Almond	5-20R	•	•	•



National Electrical Code® Section 406.12 Tamper-Resistant Receptacles in Dwelling Units.

In all areas specified in 210.52 all 125-volt, 15- and 20-amp receptacles shall be listed tamper-resistant receptacles.

All devices listed on this page conform to NEMA WD-1 and WD-6.


TECHNICAL SPECIFICATIONS

Tamper-Resistant GFCI Receptacles 2 Pole, 3 Wire Grounding 15 & 20A, 125VAC


Typical Specifications

Manufacturer's Identification: Pass & Seymour® 1595TR
 Description: Straight Blade Duplex Tamper-Resistant GFCI Receptacle
 Type: 2 Pole, 3 Wire Grounding
 Rating: 20A, 125VAC Feed Thru; 15 or 20A, 125VAC Face
 3rd Party Compliance: cULus Listed, File Number E42190; Standard UL498 Tamper-Resistant, Attachment Plugs and Receptacles UL943 GFCIs. Federal Specification WC596. Standard CSA-C22.2 No. 42, General Use Receptacles, CSA-C22.2 No. 144 GFCIs. Conforms to NEMA WD-1 and WD-6.


CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 1595TRI	Ivory	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRW	White	15A 125VAC	5-15R
<input type="checkbox"/> 1595TR	Brown	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRBK	Black	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRLA	Light Almond	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRBNCC4	Brushed Nickel	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRTI	Titanium	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRSI*	Ivory	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRSW*	White	15A 125VAC	5-15R
<input type="checkbox"/> 1595TRSLA*	Light Almond	15A 125VAC	5-15R
<input type="checkbox"/> 2095TRI	Ivory	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRW	White	20A 125VAC	5-20R
<input type="checkbox"/> 2095TR	Brown	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRGRY	Gray	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRBK	Black	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRRED	Red	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRLA	Light Almond	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRSI*	Ivory	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRSW*	White	20A 125VAC	5-20R
<input type="checkbox"/> 2095TRSLA*	Light Almond	20A 125VAC	5-20R



Dimensions for 15 & 20 Amp



Dimensions for 15 & 20 Amp With Auto-Ground



Performance

Electrical

Dielectric: Withstands 1500V minimum
 Trip Level: 4 to 6 mA
 Trip Time: .025 Second Nominal
 Frequency: 60 Hz
 Voltage: 125VAC
 Voltage Range: 102-132VAC

Mechanical

Indicator Light (LED): Red, ON when GFCI is tripped
 Terminal Identification: Terminals identified in accordance with UL498 (Hot, White, Green)
 Terminal Accommodation: #14 - #10 AWG solid or stranded copper conductor only
 Product Identification: Ratings are a permanent part of device

Environmental

Operating Temperature: -35°C to +66°C
 Maximum Humidity: 95%
 Flammability: UL94 V2

Materials

Face:	Nylon	Hex Head Grounding Screw:	Steel (Green)
Body:	Nylon	Flat Head Mounting Screws:	Zinc-Plated Steel
Contacts:	.03" Brass (.8)	Test/Reset Buttons:	Nylon
Mounting Straps:	.05" Zinc-Plated Steel (1.3)	Tamper-Resistant Shutter:	Thermoplastic
Terminal Screws:	Steel #8 - 32	Auto-Ground Clip*:	Brass Alloy C260

*Tamper-Resistant GFCIs with Auto-Ground feature.

Project
Location/Type

TECHNICAL SPECIFICATIONS

Hospital Grade Tamper-Resistant GFCI Receptacles 2 Pole, 3 Wire Grounding 15 & 20A, 125VAC

Typical Specifications

Manufacturer's Identification: Pass & Seymour® 1595HGTR


Description: Straight Blade Duplex Hospital Grade Tamper-Resistant GFCI Receptacle

Type: 2 Pole, 3 Wire Grounding


Rating: 20A, 125VAC Feed Thru; 15 or 20A, 125VAC Face

3rd Party Compliance: cULus Listed, File Number E42190, Standard UL498 Tamper-Resistant, Attachment Plugs and Receptacles UL943 GFCIs. Federal Specification WC596 Hospital Grade. Standard CSA-C22.2 No. 42, General Use Receptacles, CSA-C22.2 No. 144 GFCIs. Conforms to NEMA WD-1 and WD-6.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 1595HGTRI	Ivory	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGTRW	White	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGTR	Brown	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGTRGRY	Gray	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGTRRED	Red	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGTRLA	Light Almond	15A 125VAC	5-15R
<input type="checkbox"/> 2095HGTRI	Ivory	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGTRW	White	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGTR	Brown	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGTRGRY	Gray	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGTRRED	Red	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGTRLA	Light Almond	20A 125VAC	5-20R



Dimensions for
15 & 20 Amp



Performance

Electrical

Dielectric:	Withstands 1500V minimum
Trip Level:	4 to 6 mA
Trip Time:	.025 Second Nominal
Frequency:	60 Hz
Voltage:	125VAC
Voltage Range:	102-132VAC

Mechanical

Indicator Light (LED):	Red, ON when GFCI is tripped
Terminal Identification:	Terminals identified in accordance with UL498 (Hot, White, Green)
Terminal Accommodation:	#14 - #10 AWG solid or stranded copper conductor only
Product Identification:	Ratings are a permanent part of the device

Environmental

Operating Temperature:	-35°C to +66°C
Maximum Humidity:	95%
Flammability:	UL94 V2

Materials

Face:	Nylon	Hex Head Grounding Screw:	Steel (Green)
Body:	Nylon	Flat Head Mounting Screw:	Zinc-Plated Steel
Contacts:	.03" Brass (.8)	Test/Reset Buttons:	Nylon
Mounting Strap:	.05" Zinc-Plated Steel (1.3)	Tamper-Resistant Shutter:	Thermoplastic
Terminal Screws:	Steel #8 - 32		

Project
Location/Type

TECHNICAL SPECIFICATIONS

Hospital Grade GFCI Receptacles 2 Pole, 3 Wire Grounding 20A, 125VAC

Typical Specifications

Manufacturer's Identification: Pass & Seymour® 1595HG


Description: Straight Blade Duplex Hospital Grade GFCI Receptacle

Type: 2 Pole, 3 Wire Grounding


Rating: 20A, 125VAC Feed Thru; 15 or 20A, 125VAC Face

3rd Party Compliance: cULus Listed, File Number E42190, Standard UL498, Attachment Plugs and Receptacles UL943 GFCIs. Federal Specification WC596 Hospital Grade. Standard CSA-C22.2 No. 42, General Use Receptacles, CSA-C22.2 No. 144 GFCIs. Conforms to NEMA WD-1 and WD-6.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 1595HGI	Ivory	15A 125VAC	5-15R
<input type="checkbox"/> 1595HWG	White	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGB	Brown	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGGRY	Gray	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGRE	Red	15A 125VAC	5-15R
<input type="checkbox"/> 1595HGLA	Light Almond	15A 125VAC	5-15R
<input type="checkbox"/> 2095HGI	Ivory	20A 125VAC	5-20R
<input type="checkbox"/> 2095HWG	White	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGB	Brown	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGGRY	Gray	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGRE	Red	20A 125VAC	5-20R
<input type="checkbox"/> 2095HGLA	Light Almond	20A 125VAC	5-20R



Dimensions for
15 & 20 Amp



Performance

Electrical

Dielectric:	Withstands 1500V minimum
Trip Level:	4 to 6 mA
Trip Time:	.025 Second Nominal
Frequency:	60 Hz
Voltage:	125VAC
Voltage Range:	102-132VAC

Mechanical

Indicator Light (LED):	Red, ON when GFCI is tripped
Terminal Identification:	Terminals identified in accordance with UL498 (Hot, White, Green)
Terminal Accommodation:	#14 – #10 AWG solid or stranded copper conductor only
Product Identification:	Ratings are a permanent part of the device

Environmental

Operating Temperature:	-35°C to +66°C
Maximum Humidity:	95%
Flammability:	UL94 V2

Materials

Face:	Nylon	Terminal Screws:	Steel #8 - 32
Body:	Nylon	Hex Head Grounding Screw:	Steel (Green)
Contacts:	.03" Brass (.8)	Flat Head Mounting Screw:	Zinc-Plated Steel
Mounting Strap:	.05" Zinc-Plated Steel (1.3)	Test/Reset Buttons:	Nylon

Project
Location/Type

TECHNICAL SPECIFICATIONS


Audible Alarm Hospital Grade Tamper-Resistant GFCI

2 Pole, 3 Wire Grounding 15 & 20A, 125VAC


Typical Specifications

Manufacturer's Identification: Pass & Seymour® 1595HGTRA
 Description: Straight Blade Duplex Audible Alarm Hospital Grade Tamper-Resistant Receptacle
 Type: 2 Pole, 3 Wire Grounding
 Rating: 20A, 125VAC Feed Thru, 15A & 20A, 125VAC FACE
 3rd Party Compliance: cULus Listed, Standard UL498 Tamper-Resistant, Attachment Plugs and Receptacles UL943 GFCIs. Federal Specification WC596 Hospital Grade. Standard CSA-C22.2 No. 42, General Use Receptacles, CSA-C22.2 No. 144 GFCIs.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.	CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 1595HGTRAI	Ivory	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRAI	Ivory	20, 125VAC	5-20R
<input type="checkbox"/> 1595HGTRAW	White	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRAW	White	20, 125VAC	5-20R
<input type="checkbox"/> 1595HGTRA	Brown	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRA	Brown	20, 125VAC	5-20R
<input type="checkbox"/> 1595HGTRAGRY	Gray	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRAGRY	Gray	20, 125VAC	5-20R
<input type="checkbox"/> 1595HGTRARED	Red	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRARED	Red	20, 125VAC	5-20R
<input type="checkbox"/> 1595HGTRALA	Lt. Almond	15, 125VAC	5-15R	<input type="checkbox"/> 2095HGTRALA	Lt. Almond	20, 125VAC	5-20R



2095HGTRAW



Performance

Electrical

Dielectric: Withstands 1500V minimum
 Trip Level: 4 to 6 mA
 Trip Time: .025 Second Nominal
 Frequency: 60 Hz
 Voltage: 125VAC
 Voltage Range: 102-132VAC
 Short Circuit Rating: 10kA

Mechanical

Indicator Light (LED): Red, ON when GFCI is tripped
 Audible Alarm: 60 dB at 10 feet
 Terminal Identification: Terminals identified in accordance with UL498 (Hot, White, Green)
 Terminal Accommodation: #14 - #10 AWG solid or stranded copper conductor only
 Motor Control: Rated as a 1.5 HP motor control switch

Environmental

Operating Temperature: -35°C to +66°C
 Maximum Humidity: 95%
 Flammability: UL94 V2

Materials

Face: Nylon
 Body: Nylon
 Contacts: .03" Brass (.8)
 Mounting Strap: .05" Zinc-Plated Steel (1.3)
 Terminal Screws: Steel #8 - 32
 Flat Head Mounting Screws: Zinc-Plated Steel
 Test/Reset Buttons: Nylon

TECHNICAL SPECIFICATIONS

Project
Location/Type

TECHNICAL SPECIFICATIONS


Hospital Grade Isolated-Ground Tamper-Resistant GFCI Receptacles

2 Pole, 3 Wire Grounding 15 & 20A, 125VAC

Typical Specifications

Manufacturer's Identification: Pass & Seymour® 1595IGHGTR
 Description: Straight Blade Duplex Isolated Ground Tamper-Resistant GFCI Receptacle
 Type: 2 Pole, 3 Wire Grounding
 Rating: 20A, 125VAC Feed Thru, 15A & 20A, 125VAC FACE
 3rd Party Compliance: cULus Listed, Standard UL498 Tamper-Resistant, Attachment Plugs and Receptacles UL943 GFCIs. Federal Specification WC596 Hospital Grade. Standard CSA-C22.2 No. 42, General Use Receptacles, CSA-C22.2 No. 144 GFCIs.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.	CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 1595IGHGTRI	Ivory	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRI	Ivory	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTRW	White	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRW	White	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTR	Brown	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTR	Brown	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTRGRY	Gray	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRGRY	Gray	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTRRED	Red	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRRED	Red	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTRO	Orange	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRO	Orange	20, 125VAC	5-20R
<input type="checkbox"/> 1595IGHGTRLA	Lt. Almond	15, 125VAC	5-15R	<input type="checkbox"/> 2095IGHGTRLA	Lt. Almond	20, 125VAC	5-20R



Performance

Electrical

Dielectric: Withstands 1500V minimum
 Trip Level: 4 to 6 mA
 Trip Time: .025 Second Nominal
 Frequency: 60 Hz
 Voltage: 125VAC
 Voltage Range: 102-132VAC
 Short Circuit Rating: 10kA

Mechanical

Indicator Light (LED): Red, ON when GFCI is tripped
 Terminal Identification: Terminals identified in accordance with UL498 (Hot, White)
 Terminal Accommodation: #14 – #10 AWG solid or stranded copper conductor only
 Product Identification: Ratings are a permanent part of the device


Environmental

Operating Temperature: -35°C to +66°C
 Maximum Humidity: 95%
 Flammability: UL94 V2

Materials

Face: Nylon
 Body: Nylon
 Contacts: .03" Brass (.8)
 Mounting Strap: .05" Zinc-Plated Steel (1.3)

Terminal Screws: Steel #8 - 32
 Flat Head Mounting Screws: Zinc-Plated Steel
 Test/Reset Buttons: Nylon



TECHNICAL SPECIFICATIONS

Project
Location/Type

TECHNICAL SPECIFICATIONS

PlugTail™ Hospital Grade Tamper-Resistant GFCI Receptacles

2 Pole, 3 Wire Grounding 15 & 20A, 125VAC

Typical Specifications

Manufacturer's Identification: Pass & Seymour® PT1595HGTR
 Description: PlugTail™ Straight Blade Duplex Hospital Grade Tamper-Resistant GFCI Receptacle Type:
 2 Pole, 3 Wire Grounding
 Rating: 20A, 125VAC Feed Thru; 15 or 20A, 125VAC Face
 3rd Party Compliance: cULus Listed File Number E42190 and E140596, Standard UL498 TamperResistant, Attachment Plugs and Receptacles, UL943 GFCIs. Federal Specification WC596 Hospital Grade. Standard CSA C22.2 No. 42 General Use Receptacles, CSA C22.2 No. 144 GFCIs.
 Conforms to NEMA WD-1 and WD-6.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> PT1595HGTRI	Ivory	15A 125VAC	5-15R
<input type="checkbox"/> PT1595HGTRW	White	15A 125VAC	5-15R
<input type="checkbox"/> PT1595HGTRGRY	Gray	15A 125VAC	5-15R
<input type="checkbox"/> PT1595HGTRRED	Red	15A 125VAC	5-15R
<input type="checkbox"/> PT1595HGTRLA	Light Almond	15A 125VAC	5-15R
<input type="checkbox"/> PT2095HGTRI	Ivory	20A 125VAC	5-20R
<input type="checkbox"/> PT2095HGTRW	White	20A 125VAC	5-20R
<input type="checkbox"/> PT2095HGTRGRY	Gray	20A 125VAC	5-20R
<input type="checkbox"/> PT2095HGTRRED	Red	20A 125VAC	5-20R
<input type="checkbox"/> PT2095HGTRLA	Light Almond	20A 125VAC	5-20R

Performance

Electrical

Dielectric: Withstands 1500V minimum
 Trip Level: 4 to 6 mA
 Trip Time: .025 Second Nominal
 Frequency: 60 Hz
 Voltage: 125VAC
 Voltage Range: 102-132VAC

Mechanical

Indicator Light (LED): Red, ON when GFCI is tripped
 PlugTail Connector Identification: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid or stranded, for use with PlugTail Receptacles only
 Product Identification: Ratings are a permanent part of the device

Environmental


Operating Temperature: -35°C to +66°C
 Maximum Humidity: 95%
 Flammability: UL94 V2

PlugTail™ GFCI Receptacle Materials


Face: Nylon
 Body: Nylon
 Contacts: .03" Brass (.8)
 Mounting Strap: .05" Zinc-Plated Steel (1.3)
 Flat Head Mounting Screws: Zinc-Plated Steel
 Test/Reset Buttons: Nylon
 Tamper-Resistant Shutter: Thermoplastic

PlugTail Connector Materials


Housing: Polycarbonate
 Contacts: .030" Brass



Dimensions for 15 & 20 Amp



PTR66STR



NEMA 5-15R

NEMA 5-20R

Project
Location/Type

TECHNICAL SPECIFICATIONS


NAFTA-Compliant PlugTail™ Hospital Grade GFCI Receptacles

15 & 20A, 125VAC 2 Pole, 3 Wire Grounding


Typical Specifications

Manufacturer's Identification: Pass & Seymour® PT1595HG
 Description: PlugTail™ Straight Blade Duplex Hospital Grade NAFTA-Compliant GFCI Receptacle, Straight Blade Duplex Hospital Grade Tamper-Resistant NAFTA-Compliant GFCI Receptacle & Straight Blade Duplex Tamper-Resistant NAFTA-Compliant Nightlight/GFCI Receptacle
 Type: 2 Pole, 3 Wire Grounding
 Rating: 20A, 125VAC Feed Thru; 15 or 20A, 125VAC Face
 3rd Party Compliance: cULus Listed File Number E42190 and E140596, Standard UL498, Attachment Plugs and Receptacles, UL943 GFCIs. Federal Specification WC596, Hospital Grade. Standard CSA C22.2 No. 42 General Use Receptacles, CSA C22.2 No. 144 GFCIs. Conforms to NEMA WD-1 and WD-6.


CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
PT2095HGNAI	Ivory	20A 125VAC	5-20R
PT2095HGNAW	White	20A 125VAC	5-20R
PT2095HGNAGRY	Gray	20A 125VAC	5-20R
PT2095HGNARED	Red	20A 125VAC	5-20R
PT2095HGNALA	Light Almond	20A 125VAC	5-20R
PT1595HGTRNAI	Ivory	15A 125VAC	5-15R
PT1595HGTRNAW	White	15A 125VAC	5-15R
PT1595HGTRNAGRY	Gray	15A 125VAC	5-15R
PT1595HGTRNARED	Red	15A 125VAC	5-15R
PT1595HGTRNALA	Light Almond	15A 125VAC	5-15R
PT1595HGNTLTRNAI	Ivory	15A 125VAC	5-15R
PT1595HGNTLTRNAW	White	15A 125VAC	5-15R
PT1595HGNTLTRNARED	Red	15A 125VAC	5-15R
PT2095HGNTLTRNAI	Ivory	20A 125VAC	5-20R
PT2095HGNTLTRNAW	White	20A 125VAC	5-20R
PT2095HGNTLTRNARED	Red	20A 125VAC	5-20R



Dimensions for 15 & 20 Amp



PTRA6STR



Performance

Electrical

Dielectric: Withstands 1500V minimum
 Trip Level: 4 to 6 mA
 Trip Time: .025 Second Nominal
 Frequency: 60 Hz
 Voltage: 125VAC
 Voltage Range: 102-132VAC

Mechanical

Indicator Light (LED): Red, ON when GFCI is tripped
 PlugTail Connector Identification: #12 AWG, THHN, copper conductor, 6" leads, stripped, solid or stranded, for use with PlugTail Receptacles only
 Ratings are a permanent part of the device

Product Identification:

Environmental

Operating Temperature: -35°C to +66°C
 Maximum Humidity: 95%
 Flammability: UL94 V2

PlugTail™ GFCI Receptacle Materials

Face: Nylon
 Body: Nylon
 Contacts: .03" Brass (.8)
 Mounting Strap: .05" Zinc-Plated Steel (1.3)
 Flat Head Mounting Screws: Zinc-Plated Steel
 Test/Reset Buttons: Nylon
 Tamper-Resistant Shutter: Thermoplastic

PlugTail Connector Materials

Housing: Polycarbonate
 Contacts: .030" Brass

NAFTA-Compliant GFCI Receptacles are ideal for use on projects subject to the provisions of the Buy American Act.

Project
Location/Type