



Split Mesh Rod Closing Basket Type Slack Pulling Grips



- Use to pull when the end of the conductor is not available.
- Type of pulls: light and straight. The rod will not flex around bends.
- Single weave galvanized steel mesh with rod closing and an offset flexible eye.
- Select the grip with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.

Cat./ UPC No.	Cable Diameter Range		Maximum Rated Capacity		Eye Length		Mesh Length		Ship Weight	
	inch	mm	lbs.	kN	inch	mm	inch	mm	lbs.	kg
30658	.50 - .61	12.7 - 15.50	300	1.3	7	177.8	6	152.4	.1	.05
31024	.62 - .74	15.6 - 18.9	360	1.6	7	177.8	8	203.2	.1	.05
30660	.75 - .99	19 - 25.3	440	1.9	7	177.8	10	254	.2	.09
31026	1.00 - 1.24	25.4 - 31.5	680	3	8	203.2	12	304.8	.3	.14
30662	1.25 - 1.49	31.6 - 38.0	900	4	8	203.2	14	355.6	.5	.23
31028	1.50 - 1.74	38.1 - 44.3	1160	5.1	9	228.6	15	381	.7	.32
30664	1.75 - 1.99	44.4 - 50.7	1520	6.7	10	254	16	406.4	.9	.41
31030	2.00 - 2.49	50.8 - 63.4	1800	8	10	254	19	482.6	1.1	.50
30666	2.50 - 2.99	63.5 - 76.1	2200	9.7	10	254	20	508	1.3	.59
31032	3.00 - 3.49	76.2 - 88.8	2400	10.6	12	304.8	21	533.4	1.8	.82
30668	3.50 - 3.99	88.9 - 101.3	2400	10.6	12	304.8	24	610	1.8	.82

Closed Mesh Basket Type Slack Grips



- Use to pull extra cable for termination when the end is available.
- Type of pulls: lightweight, straight or around bends.
- Double weave, closed, galvanized steel mesh with offset flexible eye.
- Select the grip with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.

Cat./ UPC No.	Cable Diameter Range		Maximum Pulling Force		Eye Length		Mesh Length		Ship Weight	
	inch	mm	lbs.	kN	inch	mm	inch	mm	lbs.	kg
31016	.50 - .99	12.7 - 25.3	520	2.3	7	177.8	12	304.8	.4	.18
30598	1.00 - 1.24	25.4 - 31.5	800	3.5	8	203.2	15	381	.6	.27
31018	1.25 - 1.49	31.6 - 38.0	1080	4.8	8	203.2	16	406.4	.8	.36
30600	1.50 - 1.74	38.1 - 44.3	1320	5.8	9	228.6	17	431.8	1.1	.50
31020	1.75 - 1.99	44.4 - 50.7	2000	8.8	10	254	18	457.2	2	.90
30602	2.00 - 2.49	50.8 - 63.4	2200	9.7	10	254	19	482.6	2	.90
30604	2.50 - 2.99	63.5 - 76.1	2200	9.7	10	254	20	508	2	.90
30606	3.00 - 3.49	76.2 - 88.8	2900	12.8	12	304.8	21	533.4	4.6	2.09
31022	3.50 - 3.99	88.9 - 101.3	2900	12.8	12	304.8	22	558.8	4.7	2.13

Wire Caddies



905, 906 Features

- All welded steel frame.
- 6 wire spool axles with spring clip locks.
- Pre-drilled caster mounting holes.

906 Features

- Collapsible wire guide.
- Swivel caster set with 2 locking casters for easy use.

Cat. No.	UPC No.	Description
905	33024	Wire Caddy
906	33026	Wire Caddy with Casters and Wire Guide
33405	33405	Caster Set (2 swivel, 2 swivel lock)

SPECIFICATIONS

Size: 16" (406.4 mm) long, 26" (660.4 mm) wide and 17-1/2" (444.5 mm) high

Capacity: Six 500' (152.4 m) spools up to 8" (203.2 mm) in diameter of #6 thru #10 AWG 600 volt wire

Weight: 905 - 8 lbs. (3.63 kg); 906 - 10 lbs. (4.54 kg)