


Wire end ferrules with plastic collar



- Polypropylene conical cable entry
- Heat-resistant up to 105 °C
- Cable entry made from a not readily flammable material on request

For conductors from 0.14 to 150 mm² (AWG 26-300MCM)

Tin-plated copper

Dimensional tolerances to DIN 46228 part 4

Weidmüller colour code

packed loose

Ordering data


Type	Cross-section, mm ²	AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.25/10	0.25	24	10.0	6.0	0.8	1.8	8.0	light blue	500	9025740000
H0.25/12	0.25	24	12.0	8.0	0.8	1.8	10.0	light blue	500	9025760000
H0.34/10	0.34	22	10.0	6.0	0.8	2.0	8.0	turquoise	500	9025750000
H0.34/12	0.34	22	12.0	8.0	0.8	2.0	10.0	turquoise	500	9025770000
H0.5/12	0.50	20	12.0	6.0	1.0	2.6	8.0	orange	500	0409500000
H0.5/14	0.50	20	14.0	8.0	1.0	2.6	10.0	orange	500	0690700000
H0.5/16	0.50	20	16.0	10.0	1.0	2.6	12.0	orange	500	9025870000
H0.75/12	0.75	18	12.0	6.0	1.2	2.8	8.0	white	500	0409600000
H0.75/14	0.75	18	14.0	8.0	1.2	2.8	10.0	white	500	0462900000
H0.75/16	0.75	18	16.0	10.0	1.2	2.8	12.0	white	500	9025860000
H0.75/18	0.75	18	18.0	12.0	1.2	2.8	14.0	white	500	9025910000
H1.0/12	1.00	17	12.0	6.0	1.4	3.0	8.0	yellow	500	0409700000
H1.0/14	1.00	17	14.0	8.0	1.4	3.0	10.0	yellow	500	0463000000
H1.0/16	1.00	17	16.0	10.0	1.4	3.0	12.0	yellow	500	9025950000
H1.0/18	1.00	17	18.0	12.0	1.4	3.0	15.0	yellow	500	9025930000
H1.5/14	1.50	16	14.0	8.0	1.7	3.5	10.0	red	500	0463100000
H1.5/16	1.50	16	16.0	10.0	1.7	3.5	12.0	red	500	0635100000
H1.5/24	1.50	16	24.0	18.0	1.7	3.5	20.0	red	500	0565600000
H2.5/14D	2.50	14	14.0	8.0	2.2	4.2	10.0	blue	500	9019160000
H2.5/18D	2.50	14	18.0	12.0	2.2	4.2	14.0	blue	500	9019170000
H2.5/24D	2.50	14	24.0	18.0	2.2	4.2	20.0	blue	500	9019180000
H4.0/17D	4.00	12	17.0	10.0	2.8	4.8	12.0	grey	500	9019190000
H4.0/20D	4.00	12	20.0	12.0	2.8	4.8	14.0	grey	500	9019200000
H4.0/26D	4.00	12	26.0	18.0	2.8	4.8	20.0	grey	100	9019210000
H6.0/20	6.00	10	20.0	12.0	3.5	6.3	14.0	black	100	0533500000
H6.0/26	6.00	10	26.0	18.0	3.5	6.3	20.0	black	100	0565700000
H10.0/22	10.00	7	22.0	12.0	4.5	7.6	15.0	ivory	100	0534200000
H10.0/28	10.00	7	28.0	18.0	4.5	7.6	21.0	ivory	100	0565800000
H16.0/24	16.00	6	24.0	12.0	5.8	8.8	15.0	green	100	0565900000
H16.0/28	16.00	6	28.0	18.0	5.8	8.8	21.0	green	100	0566000000
H25.0/30	25.00	3	30.0	16.0	7.3	11.2	18.0	brown	50	0317000000
H25.0/36	25.00	3	36.0	22.0	7.3	11.2	24.0	brown	50	0317100000
H35.0/30	35.00	2	30.0	16.0	8.3	12.7	19.0	beige	50	0317200000
H35.0/39	35.00	2	39.0	25.0	8.3	12.7	28.0	beige	50	0317300000
H50.0/36	50.00	1	36.0	20.0	10.3	15.0	26.0	olive green	50	0444200000
H70.0/40	70.00	2/0	37.0	20.0	12.7	16.0	26.0	yellow	25	9028200000
H95.0/44	95.00	3/0	44.0	25.0	14.7	18.0	31.0	red	25	9028210000
H120.0/50	120.00	4/0	50.0	30.0	16.5	21.0	36.0	blue	25	9028220000
H150.0/54	150.00	300 MCM	54.0	32.0	18.5	23.5	38.0	yellow	25	9028230000

Weidmüller colour code

in multipack bag

Ordering data

Type	Cross-section, mm ²	AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.14/10	0.14	26	10.0	6.0	0.6	1.5	8.0	grey	500	9005180000
H0.14/12	0.14	26	12.0	8.0	0.6	1.5	10.0	grey	500	9028240000
H0.25/10	0.25	24	10.0	6.0	0.8	1.8	8.0	light blue	500	9026050000
H0.25/12	0.25	24	12.0	8.0	0.8	1.8	10.0	light blue	500	9025780000
H0.34/10	0.34	22	10.0	6.0	0.8	2.0	8.0	turquoise	500	9026030000
H0.34/12	0.34	22	12.0	8.0	0.8	2.0	10.0	turquoise	500	9025790000
H0.5/10	0.50	20	10.0	6.0	1.0	2.6	8.0	orange	500	9028260000
H0.5/14	0.50	20	14.0	8.0	1.0	2.6	10.0	orange	500	9026060000
H0.5/16	0.50	20	16.0	10.0	1.0	2.6	12.0	orange	500	9028270000
H0.75/12	0.75	18	12.0	6.0	1.2	2.8	8.0	white	500	9028280000
H0.75/14	0.75	18	14.0	8.0	1.2	2.8	10.0	white	500	9026070000
H0.75/16	0.75	18	16.0	10.0	1.2	2.8	12.0	white	500	9028290000
H0.75/18	0.75	18	18.0	12.0	1.2	2.8	14.0	white	500	9028300000
H1.0/12	1.00	17	12.0	6.0	1.4	3.0	8.0	yellow	500	9028310000
H1.0/14	1.00	17	14.0	8.0	1.4	3.0	10.0	yellow	500	9026080000
H1.0/16	1.00	17	16.0	10.0	1.4	3.0	12.0	yellow	500	9028320000
H1.0/18	1.00	17	18.0	12.0	1.4	3.0	15.0	yellow	500	9028340000
H1.5/14	1.50	16	14.0	8.0	1.7	3.5	10.0	red	500	9026090000
H1.5/16	1.50	16	16.0	10.0	1.7	3.5	12.0	red	500	9028350000
H2.5/14	2.50	14	14.0	8.0	2.2	4.2	10.0	blue	500	9026100000
H4.0/17	4.00	12	17.0	10.0	2.8	4.8	12.0	grey	250	9026010000



- Polypropylene conical cable entry
- Heat-resistant up to 105 °C
- Cable entry made from a not readily flammable material on request

For conductors from 0.5 to 2.5 mm² (AWG 22-14)
Tin-plated copper
Dimensional tolerances to DIN 46228 part 4

Weidmüller colour code

Strip of wire end ferrules

Ordering data

Type	Cross-section, mm ²	AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.5/14	0.50	20	14.0	8.0	1.0	2.6	10.0	orange	500	9004270000
H0.75/14	0.75	18	14.0	8.0	1.2	2.8	10.0	white	500	9004290000
H1.0/14	1.00	17	14.0	8.0	1.4	3.0	10.0	yellow	500	9004320000
H1.5/14	1.50	16	14.0	8.0	1.7	3.2	10.0	red	500	9004340000
H2.5/14D	2.50	14	14.0	8.0	2.2	4.0	11.0	blue	500	9004360000


Weidmüller colour code

Reel of wire end ferrules

Ordering data

Type	Cross-section, mm ²	AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.34/12	0.34	22	12.0	8.0	0.8	2.0	10.0	turquoise	5000	9004390000
H0.5/14	0.50	20	14.0	8.0	1.0	2.6	10.0	orange	5000	9005810000
H0.75/14	0.75	18	14.0	8.0	1.2	2.8	10.0	white	5000	9005820000
H1.0/14	1.00	17	14.0	8.0	1.4	3.0	11.0	yellow	5000	9005830000
H1.5/14	1.50	16	14.0	8.0	1.7	3.2	10.0	red	5000	9005840000
H2.5/14D	2.50	14	14.0	8.0	2.2	4.0	11.0	blue	3000	9005850000

Wire end ferrules with plastic collar



- Polypropylene conical cable entry
- Heat-resistant up to 105 °C
- Cable entry made from a not readily flammable material on request

For conductors from 0.5 to 50 mm² (AWG 20-1)

Tin-plated copper

Dimensional tolerances to DIN 46228 part 4

DIN colour code

packed loose

Ordering data

Type	Cross-section, mm ² AWG	L1	L2	D1	D2	Stripping length	Colour	VG*	Qty.	Order No.	
H0.5/12D	0.50	20	12.0	6.0	1.0	2.6	8.0	○ white	T 20A 001 A	500	9019000000
H0.5/14D	0.50	20	14.0	8.0	1.0	2.6	10.0	○ white	T 20A 002 A	500	9019010000
H0.5/16D	0.50	20	16.0	10.0	1.0	2.6	12.0	○ white	T 20A 003 A	500	9019020000
H0.75/12D	0.75	18	12.0	6.0	1.2	2.8	8.0	● grey	T 20A 004 A	500	9019030000
H0.75/14D	0.75	18	14.0	8.0	1.2	2.8	10.0	● grey	T 20A 005 A	500	9019040000
H0.75/16D	0.75	18	16.0	10.0	1.2	2.8	12.0	● grey	T 20A 006 A	500	9019050000
H0.75/18D	0.75	18	18.0	12.0	1.2	2.8	14.0	● grey	T 20A 007 A	500	9019060000
H1.0/12D	1.00	17	12.0	6.0	1.4	3.0	8.0	● red	T 20A 008 A	500	9019070000
H1.0/14D	1.00	17	14.0	8.0	1.4	3.0	10.0	● red	T 20A 009 A	500	9019080000
H1.0/16D	1.00	17	16.0	10.0	1.4	3.0	12.0	● red	T 20A 010 A	500	9019100000
H1.0/18D	1.00	17	18.0	12.0	1.4	3.0	15.0	● red	T 20A 011 A	500	9019110000
H1.5/14D	1.50	16	14.0	8.0	1.7	3.5	10.0	● black		500	9019120000
H1.5/16D	1.50	16	16.0	10.0	1.7	3.5	12.0	● black	T 20A 013 A	500	9019130000
H1.5/18D	1.50	16	18.0	12.0	1.7	3.5	15.0	● black	T 20A 014 A	500	9019140000
H1.5/24D	1.50	16	24.0	18.0	1.7	3.5	20.0	● black	T 20A 015 A	500	9019150000
H2.5/14D	2.50	14	14.0	8.0	2.2	4.2	10.0	● blue	T 20A 016 A	500	9019160000
H2.5/18D	2.50	14	18.0	12.0	2.2	4.2	14.0	● blue	T 20A 017 A	500	9019170000
H2.5/24D	2.50	14	24.0	18.0	2.2	4.2	20.0	● blue	T 20A 018 A	500	9019180000
H4.0/17D	4.00	12	17.0	10.0	2.8	4.8	12.0	● grey	T 20A 019 A	500	9019190000
H4.0/20D	4.00	12	20.0	12.0	2.8	4.8	14.0	● grey	T 20A 020 A	500	9019200000
H4.0/26D	4.00	12	26.0	18.0	2.8	4.8	20.0	● grey	T 20A 021 A	100	9019210000
H6.0/20D	6.00	10	20.0	12.0	3.5	6.3	14.0	● yellow	T 20A 022 A	100	9019220000
H6.0/26D	6.00	10	26.0	18.0	3.5	6.3	20.0	● yellow	T 20A 023 A	100	9019230000
H10.0/22D	10.00	7	22.0	12.0	4.5	7.6	15.0	● red	T 20A 024 A	100	9019240000
H10.0/28D	10.00	7	28.0	18.0	4.5	7.6	21.0	● red	T 20A 025 A	100	9019250000
H16.0/24D	16.00	6	24.0	12.0	5.8	8.8	15.0	● blue	T 20A 026 A	100	9019260000
H16.0/28D	16.00	6	28.0	18.0	5.8	8.8	21.0	● blue	T 20A 027 A	100	9019270000
H25.0/30D	25.00	3	30.0	16.0	7.3	11.2	18.0	● yellow	T 20A 028 A	50	9019280000
H25.0/36D	25.00	3	36.0	22.0	7.3	11.2	24.0	● yellow	T 20A 030 A	50	9019300000
H35.0/30D	35.00	2	30.0	18.0	8.3	12.7	21.0	● red	T 20A 032 A	50	9019320000
H35.0/30D	35.00	2	30.0	16.0	8.3	12.7	19.0	● red	T 20A 031 A	50	9019310000
H35.0/39D	35.00	2	39.0	25.0	8.3	12.7	28.0	● red	T 20A 033 A	50	9019330000
H50.0/36D	50.00	1	36.0	20.0	10.3	15.0	26.0	● blue	T 20A 034 A	50	9019340000
H50.0/40D	50.00	1	40.0	25.0	10.3	15.0	31.0	● blue	T 20A 035 A	50	9019350000

DIN colour code

in multipack bag

Ordering data

Type	Cross-section, mm ² AWG	L1	L2	D1	D2	Stripping length	Colour	VG*	Qty.	Order No.	
H0.5/14D	0.50	20	14.0	8.0	1.0	2.6	10.0	○ white	T 20A 002 A	500	9019400000
H0.75/14D	0.75	18	14.0	8.0	1.2	2.8	10.0	● grey	T 20A 005 A	500	9019410000
H1.0/14D	1.00	17	14.0	8.0	1.4	3.0	10.0	● red	T 20A 009 A	500	9019420000
H1.5/14D	1.50	16	14.0	8.0	1.7	3.5	10.0	● black		500	9019430000
H1.5/24D	1.50	16	24.0	18.0	1.7	3.5	20.0	● black	T 20A 015 A	500	9004140000
H2.5/14	2.50	14	14.0	8.0	2.2	4.2	10.0	● blue	T 20A 016 A	500	9026100000
H4.0/17	4.00	12	17.0	10.0	2.8	4.8	12.0	● grey	T 20A 019 A	250	9026010000

DIN colour code


Strip of wire end ferrules

Ordering data

Type	Cross-section, mm ² AWG	L1	L2	D1	D2	Stripping length	Colour	VG*	Qty.	Order No.	
H0.5/14D	0.50	20	14.0	8.0	1.0	2.6	10.0	○ white	T 20A 002 A	500	9004280000
H0.75/14D	0.75	18	14.0	8.0	1.2	2.8	10.0	● grey	T 20A 005 A	500	9004300000
H1.0/14D	1.00	17	14.0	8.0	1.4	3.0	10.0	● red	T 20A 009 A	500	9004330000
H1.5/14D	1.50	16	14.0	8.0	1.7	3.2	10.0	● black	T 20A 012 A	500	9004350000
H2.5/14D	2.50	14	14.0	8.0	2.2	4.0	11.0	● blue		500	9004360000

VG* = Military designation according to VG 96933-20

Twin-wire end ferrules with plastic collar



- Polypropylene conical cable entry
- Heat-resistant up to 105 °C
- Cable entry made from a not readily flammable material on request

For conductors from 2 No. 0.5 to 2 No. 16 mm² (2 No. AWG 20 to 2 No. AWG 6)

Tin-plated copper

Dimensional tolerances to DIN 46228 part 4

Weidmüller colour code

packed loose

Ordering data


Type	Cross-section, mm ² AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.5/15	0.50	20	15.0	8.0	1.4	11.0	● orange	500	9037200000
H0.5/16.5	0.50	20	16.0	10.0	1.4	13.0	● orange	500	9037210000
H0.5/18.5	0.50	20	19.0	12.0	1.4	15.0	● orange	500	9037220000
H0.75/15	0.75	18	15.0	8.0	1.7	11.0	○ white	500	9037230000
H0.75/17	0.75	18	17.0	10.0	1.7	13.0	○ white	500	9037240000
H0.75/19S	0.75	18	19.0	12.0	1.4	21.0	○ white	500	9202820000
H0.75/24.5	0.75	18	24.0	18.0	1.7	21.0	○ white	500	9037250000
H1.0/15	1.00	17	15.0	8.0	2.0	12.0	● yellow	500	9037260000
H1.0/15S	1.00	17	16.0	8.0	2.2	12.0	● yellow	500	9018690000
H1.0/20	1.00	17	19.0	12.0	2.0	16.0	● yellow	500	9037270000
H1.0/25.6	1.00	17	25.0	18.0	2.0	22.0	● yellow	500	9037280000
H1.5/16	1.50	16	16.0	8.2	2.2	11.0	● red	500	9037290000
H1.5/20	1.50	16	20.0	12.0	2.2	15.0	● red	500	9037300000
H1.5/25.6	1.50	16	26.0	18.0	2.2	21.0	● red	100	9037310000
H2.5/18.5D	2.50	14	19.0	10.0	2.8	13.0	● blue	500	9037500000
H2.5/20.5D	2.50	14	21.0	12.0	2.8	15.0	● blue	100	9037510000
H2.5/26.5D	2.50	14	27.0	18.0	2.8	21.0	● blue	100	9037520000
H4.0/22D	4.00	12	22.0	12.0	3.5	15.0	● grey	100	9037530000
H4.0/28D	4.00	12	28.0	18.0	3.5	21.0	● grey	100	9037540000
H6.0/25	6.00	10	25.0	12.0	4.5	20.0	● black	100	9037320000
H6.0/29	6.00	10	29.0	18.0	4.5	24.0	● black	100	9037330000
H10.0/24S	10.00	7	24.0	12.0	6.5	17.0	● ivory	100	9018860000
H10.0/26	10.00	7	24.0	12.0	5.8	17.0	● ivory	100	9037340000
H10.0/30	10.00	7	30.0	18.0	5.8	23.0	● ivory	100	9037350000
H10.0/30S	10.00	7	30.0	18.0	6.5	23.0	● ivory	100	9018870000
H16.0/29	16.00	6	29.0	16.0	8.3	20.0	● green	50	9037360000
H16.0/38	16.00	6	38.0	25.0	8.3	29.0	● green	50	9037370000

Weidmüller colour code

in multipack bag

Ordering data

Type	Cross-section, mm ² AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.5/15	0.50	20	15.0	8.0	1.4	11.0	● orange	500	9004440000
H0.75/15	0.75	18	15.0	8.0	1.7	11.0	○ white	500	9018510000
H0.75/17	0.75	18	17.0	10.0	1.7	13.0	○ white	500	9004900000
H1.0/15	1.00	17	15.0	8.0	2.0	12.0	● yellow	500	9018530000
H1.0/15S	1.00	17	16.0	8.0	2.2	12.0	● yellow	500	9018650000
H1.0/20	1.00	17	19.0	12.0	2.0	16.0	● yellow	500	9004910000
H1.5/16	1.50	16	16.0	8.2	2.2	11.0	● red	500	9004410000
H1.5/20	1.50	16	20.0	12.0	2.2	15.0	● red	500	9004920000
H2.5/18.5D	2.50	14	19.0	10.0	2.8	13.0	● blue	250	9004430000
H2.5/20.5D	2.50	14	21.0	12.0	2.8	15.0	● blue	250	9004740000
H4.0/22D	4.00	12	22.0	12.0	3.5	15.0	● grey	100	9004730000
H6.0/25	6.00	10	25.0	12.0	4.5	20.0	● black	100	9004930000
H10.0/26	10.00	7	24.0	12.0	5.8	17.0	● ivory	100	9004940000



For conductors 0.25-185 mm² (AWG 24-350MCM)
Material: tin-plated copper
Dimensional tolerances to DIN 46228 part 1

without plastic collar

packed loose

Ordering data

Type	Cross-section, mm ²	AWG	L1	L2	D1	D2	Stripping length	Colour	Qty.	Order No.
H0.25/5	0.25	24	5.0		0.7	1.6	5.0		1000	9018910000
H0.5/10	0.50	20	10.0		1.0	2.1	10.0		1000	9004050000
H0.5/6	0.50	20	6.0		1.0	2.1	6.0		1000	0282600000
H0.75/10	0.75	18	10.0		1.2	2.3	10.0		1000	0542500000
H0.75/6	0.75	18	6.0		1.2	2.3	6.0		1000	0282700000
H1.0/10	1.00	17	10.0		1.4	2.5	10.0		1000	0282800000
H1.0/6	1.00	17	6.0		1.4	2.5	6.0		1000	0372600000
H1.5/7	1.50	16	7.0		1.7	2.8	7.0		1000	0372700000
H1.5/10	1.50	16	10.0		1.7	2.8	10.0		1000	0186500000
H1.5/12	1.50	16	12.0		1.7	2.8	12.0		1000	9004060000
H1.5/18	1.50	16	18.0		1.7	2.8	18.0		1000	9004070000
H2.5/7	2.50	14	7.0		2.2	3.4	7.0		1000	0373000000
H2.5/10	2.50	14	10.0		2.2	3.4	10.0		1000	9004080000
H2.5/12	2.50	14	12.0		2.2	3.4	12.0		1000	0186100000
H2.5/18	2.50	14	18.0		2.2	3.4	18.0		1000	9004090000
H4/9	4.00	12	9.0		2.8	4.0	9.0		500	0373100000
H4.0/15	4.00	12	15.0		2.8	4.0	15.0		500	9004100000
H4.0/12	4.00	12	12.0		2.8	4.0	12.0		1000	0244100000
H4.0/18	4.00	12	18.0		2.8	4.0	18.0		500	9004110000
H6.0/10	6.00	10	10.0		3.5	4.7	10.0		500	9004120000
H6.0/12	6.00	10	12.0		3.5	4.7	12.0		500	0191900000
H6.0/15	6.00	10	15.0		3.5	4.7	15.0		500	0124700000
H6.0/18	6.00	10	18.0		3.5	4.7	18.0		500	9004130000
H10.0/12	10.00	7	12.0		4.5	5.8	12.0		500	0282900000
H10.0/15	10.00	7	15.0		4.5	5.8	15.0		500	0124800000
H10.0/18	10.00	7	18.0		4.5	5.8	18.0		500	0379300000
H16.0/12	16.00	6	12.0		5.8	7.5	12.0		500	0492500000
H16.0/15	16.00	6	15.0		5.8	7.5	15.0		500	0124300000
H16.0/18	16.00	6	18.0		5.8	7.5	18.0		100	0375200000
H16.0/25	16.00	6	25.0		5.8	7.5	25.0		100	9004150000
H16.0/32	16.00	6	32.0		5.8	7.5	32.0		100	9004160000
H25.0/15	25.00	3	15.0		7.3	9.5	15.0		250	0124400000
H25.0/18	25.00	3	18.0		7.3	9.5	18.0		100	0375300000
H25.0/25	25.00	3	25.0		7.3	9.5	25.0		250	9004170000
H25.0/32	25.00	3	32.0		7.3	9.5	32.0		100	9004180000
H35.0/18	35.00	2	18.0		8.3	11.0	18.0		100	0368900000
H35.0/25	35.00	2	25.0		8.3	11.0	25.0		100	9004190000
H35.0/30	35.00	2	30.0		8.3	11.0	30.0		100	9451000000
H35.0/32	35.00	2	32.0		8.3	11.0	32.0		100	9004200000
H50/18	50.00	1	18.0		10.3	13.0	18.0		100	9004210000
H50/25	50.00	1	25.0		10.3	13.0	25.0		100	9025880000
H50/32	50.00	1	32.0		10.3	13.0	32.0		100	9004220000
H70.0/25	70.00	2/0	25.0		12.5	15.0	25.0		50	9004230000
H70.0/32	70.00	2/0	32.0		12.5	15.0	32.0		50	9004240000
H95.0/25	95.00	3/0	25.0		14.5	17.0	25.0		50	9004250000
H95.0/32	95.00	3/0	32.0		14.5	17.0	32.0		50	9004260000
H120.0/32	120.00	4/0	32.0		16.5	19.0	32.0		25	9036240000
H150.0/32	150.00	300 MCM	32.0		18.5	21.0	32.0		25	9036250000
H185.0/32	185.00	350 MCM	32.0		20.0	23.5	32.0		25	9036260000