

PVC-Coated Conduit Couplings

Corrosion-protected connections for conduit sections.

OCAL-BLUE Couplings

- Nominal .002" (2 mil) blue urethane coating on interior and threads
- Minimum .040" (40 mil) PVC coating bonded to exterior — in your choice of blue, white, gray or custom colors
- Straight threads (NPS)
- Molded ribs on outer coating for easy installation (up to and including 4" trade size)
- Pressure-sealing sleeves protect your connection






Ocal® Corrosion Protection for Electrical Conduit and Fittings

CAT. NO.		COUPLING SIZE IN. METRIC SIZE DESIGNATOR*	MINIMUM LENGTH OF METAL IN. MM	TOTAL MINIMUM LENGTH INCLUDING SLEEVE IN. MM	WEIGHT STEEL ONLY LBS. KG
STEEL	ALUMINUM				
CPL1/2-	CPL1/2SA-	½	1.50	3.75	.13
CPL3/4-	CPL3/4SA-	¾	1.53	3.75	.19
CPL1-	CPL1SA-	1	1.91	4.94	0.33
CPL1-1/4-	CPL1-1/4SA-	1¼	1.91	5.50	0.43
CPL1-1/2-	CPL1-1/2SA-	1½	1.91	5.75	0.56
CPL2-	CPL2SA-	2	1.94	5.94	0.77
CPL2-1/2-	CPL2-1/2SA-	2½	2.88	6.88	1.85
CPL3-	CPL3SA-	3	3.03	7.03	2.70
CPL3-1/2-	CPL3-1/2SA-	3½	3.09	7.09	3.78
CPL4-	CPL4SA-	4	3.19	7.19	3.08
CPL5-	CPL5SA-	5	3.37	7.37	5.00
CPL6-	CPL6SA-	6	3.44	7.44	8.00
		155	87.29	188.89	3.60

NOTE – Inches and pounds are indicated in bold type. Metric measure is directly below bold type.

* Metric size designator (ANSI C80.1-1994).

Cat. No.	Size	Material	Color
CPL3/4	¾	SA	B
		Blank = Steel	_ = space for color identifier
		SA = Aluminum	G = Gray 
			W = White 
			B = Blue 
Catalog No. Example:			
CPL1SA-B is a 1" aluminum coupling coated in blue PVC.			
Custom colors also available.			