



# UL 98 Fused Rotary Disconnect Switches—30A

Standard Class J

For a Complete Assembly, Please Select:

SWITCH		<b>Switch</b>											
		<b>Amp Rating</b>	<b>Fuse Class</b>	<b>No. of Poles</b>	<b>SCCR</b>	<b>Max Horsepower Rating</b>					<b>Wire Size</b>	<b>Wire Type</b>	<b>Part Number</b>
					<b>1-Phase 220/240Vac</b>	<b>220/240Vac</b>	<b>3-Phase 440/480Vac</b>	<b>600 Vac</b>	<b>DC*</b>				
		30	J	2	200kA	3	-	-	-	3	5	#14-10 Sol #14-6 Str	75°C Cu
	30	J	3	200kA	-	7.5	15	20	3	5	#14-10 Sol #14-6 Str	75°C Cu	RDF30J-3
	30	J	4	200kA	-	7.5	15	20	3	5	#14-10 Sol #14-6 Str	75°C Cu	RDF30J-4
	* DC Ratings use two poles in series.												
+													
HANDLE		<b>Direct Mount Handle - mounts directly to switch, no shaft required</b>											
		<b>For Switch Part Number</b>		<b>Color</b>	<b>Test Function</b>	<b>Padlockable</b>						<b>Part Number</b>	
		All Switches		Black	Y	Y - On Switch						DIR-07	
	or												
		<b>External Front Operated Pistol Handles - shaft required</b>											
		<b>NEMA Type</b>	<b>Color</b>	<b>Test Function</b>	<b>Padlockable</b>	<b>Defeatable</b>						<b>Part Number</b>	
		1, 3R, 12	Black	N	Y	Y						H12-05B	
		1, 3R, 12	Red/Yellow	N	Y	Y						H12-05R	
		1, 3R, 4, 4X, 12	Black	N	Y	Y						H4X-05B	
		1, 3R, 4, 4X, 12	Red/Yellow	N	Y	Y						H4X-05R	
	1, 3R, 4, 4X, 12	Black	Y	Y	Y						H4X-05TB		
	1, 3R, 4, 4X, 12	Red/Yellow	Y	Y	Y						H4X-05TR		
or		<b>Metallic Hasp (Heavy Duty) External Front Operated Pistol Handles - shaft required</b>											
	<b>NEMA Type</b>	<b>Color</b>	<b>Test Function</b>	<b>Padlockable</b>	<b>Defeatable</b>						<b>Part Number</b>		
	1, 3R, 4, 4X, 12	Black	N	Y	Y						H4X-05BHD		
	1, 3R, 4, 4X, 12	Red/Yellow	N	Y	Y						H4X-05RHD		
	<b>External Right Side Operated Pistol Handles - shaft required</b>												
	<b>NEMA Type</b>	<b>Color</b>	<b>Test Function</b>	<b>Padlockable</b>	<b>Defeatable</b>						<b>Part Number</b>		
	1, 3R, 4, 4X, 12	Black	N	Y	N/A						H4X-05SB		
	1, 3R, 4, 4X, 12	Red/Yellow	N	Y	N/A						H4X-05SR		
	<b>Shafts for Pistol Handles</b>												
	<b>Length in (mm)</b>	<b>Mounting Depth (X) in (mm)</b>							<b>Part Number</b>				
	7.9 (200)	5.30~9.06 (135~230)							SH5-200				
	12.6 (320)	5.30~13.78 (135~350)							SH5-320				
	15.7 (400)	5.30~16.93 (135~430)							SH5-400				
OR													
	<b>Flange Handle<sup>(1)</sup> - requires shaft operated mechanism or cable operated mechanism + cable</b>												
	<b>NEMA Type</b>	<b>Flange Style</b>	<b>Test Function</b>	<b>Padlockable</b>	<b>Defeatable</b>						<b>Part Number</b>		
	1, 3R, 4, 12	Standard	N	Y	Y						FLH1		
	1, 3R, 4, 4X, 12	Chrome Plated	N	Y	Y						FLH2		
	<b>Shaft Operated Flange Mechanism<sup>(2)</sup> - includes shaft</b>												
	<b>For Enclosure Depth - in (mm)</b>									<b>Part Number</b>			
	6~24 (152~613)									FLRM			
	<b>Cable Operated Flange Mechanism and Cable - must select Mechanism<sup>(3)</sup> and Cable<sup>(4)</sup></b>												
	<b>Item / Length</b>									<b>Part Number</b>			
	Cable Mechanism									FLCM			
	36" (900mm) Cable									FLC36			
	60" (1500mm) Cable									FLC60			
	120" (3000mm) Cable									FLC120			
OR													
	<b>NFPA Through the Door Handle Kit - to be used with selector handle or front pistol handle</b>												
	<b>Color</b>	<b>Test Function</b>	<b>Padlockable</b>	<b>Defeatable</b>								<b>Part Number</b>	
	Red	N	Y	N								H79-2	