

Double-Braided Composite Rope for high force cable pullers



- Custom made to Greenlee specifications to provide 4:1 Safety Factor required for cable pulling.
- Double-braided inner core with an extra double-braided outer jacket for added strength and less stretch; white with green tracer.
- Rot and mildew resistant.
- Factory spliced eyes at both ends.
- Lowest stretch.
- Select a rope with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.



Rope Diameter	Rope Length		Cat./UPC No.	Maximum Rated		Average		Weight		Rope Stand
				Capacity		Breaking Strength		lbs.	kg	
FOR THE 640 PULLER										
9/16" (14.3 mm)	300'	91 m	35283	4,000 lbs.	17.8 kN	16,000 lbs.	71.1 kN	28	12.7	644
	600'	182 m	35284	4,000 lbs.	17.8 kN	16,000 lbs.	71.1 kN	63	28.6	644
	1,200'	365 m	35285	4,000 lbs.	17.8 kN	16,000 lbs.	71.1 kN	130	59	†
FOR THE 6001 PULLER										
3/4" (19.1 mm)	300'	91 m	35098	6,500 lbs.	28.9 kN	26,000 lbs.	115.6 kN	58	26.3	644
	600'	182 m	35100	6,500 lbs.	28.9 kN	26,000 lbs.	115.6 kN	113	51.3	654
	1,200'	365 m	35101	6,500 lbs.	28.9 kN	26,000 lbs.	115.6 kN	230	104.3	†
FOR THE 6800 PULLER										
7/8" (22.2 mm)	300'	91 m	34136	8,000 lbs.	35.6 kN	32,000 lbs.	142.3 kN	90	40.8	654
	600'	182 m	34137	8,000 lbs.	35.6 kN	32,000 lbs.	142.3 kN	178	80.7	654
	1,200'	365 m	34138	8,000 lbs.	35.6 kN	32,000 lbs.	142.3 kN	359	163.3	†

† This rope does not fit on a rope stand. Use reel jacks and a spindle to dispense. See pages 132-133.

Multiplex Cable Pulling Rope for low force cable pullers



- Strong, white polyester braided rope with green tracer.
- Rot and mildew resistant.
- Packed on sturdy reel.
- Factory spliced eyes at both ends.
- Low stretch.
- Select a rope with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force.



Rope Diameter	Rope Length		Cat./UPC No.	Maximum Rated		Average		Weight		Rope Stand
				Capacity		Breaking Strength		lbs.	kg	
FOR THE 805 PULLER										
3/8" (9.5 mm)	100'	30 m	34121	800 lbs.	3.6 kN	3700 lbs.	16.4 kN	5.6	2.5	405
	300'	91 m	34122	800 lbs.	3.6 kN	3700 lbs.	16.4 kN	14.3	6.5	406
	600'	182 m	34123	800 lbs.	3.6 kN	3700 lbs.	16.4 kN	31.0	14.3	644
	1,200'	365 m	34124	800 lbs.	3.6 kN	3700 lbs.	16.4 kN	60.0	27.2	644
FOR THE 446 PULLER										
1/2" (12.7 mm)	300'	91 m	480 / 31529	1,200 lbs.	5.3 kN	6400 lbs.	28.4 kN	21	9.5	406
	600'	182 m	481 / 31530	1,200 lbs.	5.3 kN	6400 lbs.	28.4 kN	50	22.7	644
	1,200'	365 m	482 / 31531	1,200 lbs.	5.3 kN	6400 lbs.	28.4 kN	104*	47.2	†
FOR THE 2001 PULLER										
5/8" (15.9 mm)	300'	91 m	483 / 31532	2,000 lbs.	8.9 kN	10,000 lbs.	44.4 kN	34	15.4	644
	600'	182 m	484 / 31533	2,000 lbs.	8.9 kN	10,000 lbs.	44.4 kN	75	34	644
	1,200'	365 m	485 / 31534	2,000 lbs.	8.9 kN	10,000 lbs.	44.4 kN	142	64.4	†
3/4" (19.1 mm)	300'	91 m	6005 / 29910	2,000 lbs.	8.9 kN	12,500 lbs.	55.6 kN	58	26.3	644
	600'	182 m	6015 / 30031	2,000 lbs.	8.9 kN	12,500 lbs.	55.6 kN	113	51.3	654
	1,200'	365 m	6025 / 30039	2,000 lbs.	8.9 kN	12,500 lbs.	55.6 kN	230	104.3	†

† This rope does not fit on a rope stand. Use reel jacks and a spindle to dispense. See pages 126-127.

Note: Rope is a very critical link in the cable pulling system.