



Connectors designed for every application

Based on 2012 data available from Epicor/Vista.



Twister[®] Wire Connectors

The industry's premier wire connector. Just three models accommodate the majority of common wiring configurations from 22 through 6 AWG. The ribbed cap provides a secure grip and swept wings offer extra leverage. A patented square-wire spring provides safe, secure connections.

The original twist-on wire connector features a positive-grip design for easy installation. Five color-coded models cover hundreds of wire combinations from 22 through 6 AWG. The fixed square-wire spring provides a secure connection that won't relax over time.

Wire-Nut[®] Wire Connectors



The next step in IDEAL wire connector innovation. Three models accommodate a wide range of circuit and fixture wiring combinations from 18 through 6 AWG. Built-in, contoured wings provide extra leverage on maximum wire combinations. And the live-action spring expands to accept a broader range of wire shapes and sizes.



Wing-Nut[®] Wire Connectors

Contoured Classic Fin™ design provides a secure grip for extra torque. Three models cover a full range of wire sizes from 22 through 6 AWG. The square-wire spring locks onto conductors for fast, secure connections. The low-profile shape allows easy handling and installation.

B-CAP[®] Wire Connectors



WeatherProof[®] / UnderGround[®] Wire Connectors

Twist-on connectors for underground and wet location installations. Covers a wide range of wire sizes from 22 through 6 AWG. Features non-hardening silicone sealant to ensure safe, moisture-free electrical connections. UL Listed and CSA Certified for damp/wet and direct burial applications.

The only aluminum-to-copper twist-on wire connector. Specially formulated compound reduces corrosion build-up on aluminum conductors for better conductivity and cooler connections. UL Listed and CSA Certified for aluminum-to-copper connections.

Twister[®] Al/Cu Wire Connectors





Wire Range Chart

Model: Wire Combinations:

Twister®	2 #22	3 #22	2 #20	3 #20	2 #18	2 #16	3 #16	2 #14	3 #14	2 #12	4 #14	3 #12	4 #12	3 #10	5 #12	4 #10	2 #6		
340° Lt. Blue	MIN. 2 #22				MAX. 3 #12														
341° Tan	MIN. 3 #22			MAX. 3 #10															
344° Red/Yellow					MIN. 2 #18												MAX. 4 #10		
342° Gray									MIN. 3 #14				MAX. 2 #8 w/ 2 #12						
Wire-Nut®																			
71B° Gray (300V)	MIN. 2 #22 Str.			MAX. 2 #16															
72B° Blue (300V)	MIN. 2 #22				MAX. 3 #16														
73B° Orange				MIN. 1 #18 w/ 1 #20										MAX. 2 #14					
74B° Yellow					MIN. 2 #18										MAX. 4 #14 w/ 1 #18				
76B° Red								MIN. 2 #14				MAX. 4 #12							
Wing-Nut®																			
451° Yellow					MIN. 2 #18										MAX. 3 #12				
452° Red					MIN. 2 #18														MAX. 4 #10
454° Blue													MIN. 3 #12				MAX. 1 #6 w/ 2 #8		
B-CAP®																			
B1 Yellow				MIN. 3 #20										MAX. 3 #12					
B2 Red					MIN. 2 #18										MAX. 5 #12				
B4 Blue											MIN. 2 #12				MAX. 2 #6				
B-Twist™																			
BT2™ Red					MIN. 2 #18										MAX. 2 #8				
WingTwist™																			
WT51 Yellow					MIN. 2 #18										MAX. 3 #12				
WT41 Tan	MIN. 2 #20			MAX. 3 #10															
WT52 Red								MIN. 2 #14				MAX. 5 #12							
WT54 Blue													MIN. 3 #12				MAX. 2 #6		
WireTwist™																			
WT1 Gray (300V)	MIN. 3 #22		MAX. 2 #16																
WT2 Blue (300V)				MIN. 3 #20				MAX. 3 #16											
WT3 Orange					MIN. 2 #18				MAX. 2 #14										
WT4 Yellow					MIN. 2 #18										MAX. 2 #12				
WT6 Red								MIN. 2 #14				MAX. 4 #12							
WeatherProof®																			
61° Gray/Orange	MIN. 2 #20			MAX. 2 #14															
62° Gray/Red					MIN. 2 #18										MAX. 3 #10				
63° Gray/Dark Blue									MIN. 3 #14				MAX. 5 #10						
UnderGround®/MudBug®																			
60° Gray/Blue	MIN. 1 #20 w/ 1 #18										MAX. 1 #10 w/ 2 #12								
64° Gray/Dark Blue						MIN. 2 #18 Sol.										MAX. 3 #10			
66° Gray/Dark Blue													MIN. 3 #12				MAX. 2 #6 w/ 1 #10		
60° Yellow	MIN. 1 #20 w/ 1 #18			MAX. 1 #10 w/ 2 #12															
64° Yellow					MIN. 2 #18 Sol.										MAX. 3 #10				

2 #22 3 #22 2 #20 3 #20 2 #18 2 #16 3 #16 2 #14 3 #14 2 #12 4 #14 3 #12 4 #12 3 #10 5 #12 4 #10 2 #6