

Available
Now

LED Ceiling Luminaires

Solutions that are illuminating!

- ▶ Low-profile white frosted acrylic diffusers
- ▶ Uses less energy than fluorescent lights, lasts longer and is maintenance free
- ▶ Easy installation



Ceiling Luminaire Selection

Order code	Description	Shape	Colour temp. (K)	Wattage (W)	Input voltage range (V)	Size (in.)	CRI	Average Life (hrs)	Initial Lumens (lm)	Lens type
63298	LED/CL11/15W/30K/FM/RND/STD	Round	3 000	15	120	11	80	50 000	1 050	Acrylic
63299	LED/CL11/15W/40K/FM/RND/STD	Round	4 000	15	120	11	80	50 000	1 000	Acrylic
63300	LED/CL11/15W/30K/FM/SQR/STD	Square	3 000	15	120	11	80	50 000	1 050	Acrylic
63301	LED/CL11/15W/40K/FM/SQR/STD	Square	4 000	15	120	11	80	50 000	1 000	Acrylic
63302	LED/CL14/25W/30K/FM/RND/STD	Round	3 000	25	120	14	80	50 000	1 700	Acrylic
63303	LED/CL14/25W/40K/FM/RND/STD	Round	4 000	25	120	14	80	50 000	1 650	Acrylic
63304	LED/CL14/25W/30K/FM/SQR/STD	Square	3 000	25	120	14	80	50 000	1 700	Acrylic
63305	LED/CL14/25W/40K/FM/SQR/STD	Square	4 000	25	120	14	80	50 000	1 650	Acrylic

[CLICK HERE](#)

For more information on our complete line of LED Ceiling Luminaire offering



For a complete list of ENERGY STAR qualified products, please visit www.standardpro.com