

Door coupling rotary handles for North America

Difference to normal IEC handles:


Door opening only possible with active rotation beyond the 0 position.


Door coupling rotary handles


Complete including rotary drive and coupling parts

Extension shaft additionally required.

Degree of protection IP66/UL/CSA type 4X,

		For use with	Part no. Article no. when ordered separately	Std. pack	Note
Standard, black/grey					
	Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1, N(S)1	NZM1-XTVDV-NA 100683	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on.
		NZM2, N(S)2	NZM2-XTVDV-NA 100684	1 off	
		NZM3, N(S)3	NZM3-XTVDV-NA 100685	1 off	
		NZM4, N(S)4	NZM4-XTVDV-NA 100686	1 off	

Red-yellow for emergency witching off					
	Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1, N(S)1	NZM1-XTVDVR-NA 271449	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on.
		NZM2, N(S)2	NZM2-XTVDVR-NA 271450	1 off	
		NZM3, N(S)3	NZM3-XTVDVR-NA 271451	1 off	
		NZM4, N(S)4	NZM4-XTVDVR-NA 271452	1 off	



Extension shaft

		For use with	Part no. Article no. when ordered separately	Std. pack	Note
400 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4)		NZM1/2-XV4 261232	1 off	can be cut to required length.
			NZM3/4-XV4 261234	1 off	
			NZM4(-4), N(S)4(-4)		
600 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4)		NZM1/2-XV6 260191	1 off	
			NZM3/4-XV6 260193	1 off	
			NZM4(-4), N(S)4(-4)		

For maximum shaft length 60 mm

Part no.

Article no. when ordered separately Std. pack

Note

Extremely narrow fittings

Part no.

Article no. when ordered separately Std. pack

Note

NZM1-XTVDV-60-NA 100667	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. 	NZM1-XTVDV-0-NA 100675	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on.
NZM2-XTVDV-60-NA 100668	1 off		NZM2-XTVDV-0-NA 100676	1 off	
NZM3-XTVDV-60-NA 100669	1 off		NZM3-XTVDV-0-NA 100677	1 off	
NZM4-XTVDV-60-NA 100670	1 off		NZM4-XTVDV-0-NA 100678	1 off	
		NZM...-XTVDV-60-NA <ul style="list-style-type: none"> • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 			
NZM1-XTVDVR-60-NA 100671	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. 	NZM1-XTVDVR-0-NA 100679	1 off	Door interlock <ul style="list-style-type: none"> • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on.
NZM2-XTVDVR-60-NA 100672	1 off		NZM2-XTVDVR-0-NA 100680	1 off	
NZM3-XTVDVR-60-NA 100673	1 off		NZM3-XTVDVR-0-NA 100681	1 off	
NZM4-XTVDVR-60-NA 100674	1 off		NZM4-XTVDVR-0-NA 100682	1 off	
		NZM...-XTVDV-60-NA <ul style="list-style-type: none"> • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on. 			NZM...-XTVDVR-0-NA <ul style="list-style-type: none"> • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on.