Door coupling rotary handles

Complete including rotary drive and coupling parts
An additional extension shaft is necessary with the NZM...-XT(V)D(V)(R)(-60) part numbers
Degree of protection IP66/UL/CSA type 4X

	For use with	Part no. Article no. when ordered separately	Std. pack	Note
Standard, black/grey				
 Lockable in 0 position on handle with up to 3 padlocks. With door interlock.	NZM1(-4), PN1(-4), N1(-4)	**NZM1-XTVD** 260166	1 off	**Door interlock** • Not defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)** • External warning plate/ designation label can be clipped on
	NZM2(-4), PN2(-4), N2(-4)	**NZM2-XTVD** 260168	1 off	
	NZM3(-4), PN3(-4), N3(-4)	**NZM3-XTVD** 260170	1 off	
	NZM4(-4), N4(-4)	**NZM4-XTVD** 266614	1 off	
 Lockable on handle and switch with up to 3 padlocks. Can be locked in 0 position, with adequate modification also in I position. With door interlock. Lockable on switch in 0 position.	NZM1(-4), PN1(-4), N1(-4)	**NZM1-XTVDV** 260172	1 off	
	NZM2(-4), PN2(-4), N2(-4)	**NZM2-XTVDV** 260174	1 off	
	NZM3(-4), PN3(-4), N3(-4)	**NZM3-XTVDV** 260176	1 off	
	NZM4(-4), N4(-4)	**NZM4-XTVDV** 266616	1 off	
Red-yellow for emergency witching off				
 Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1(-4), PN1(-4), N1(-4)	**NZM1-XTVDVR** 260178	1 off	**Door interlock** • Not defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)** • External warning plate/ designation label can be clipped on
	NZM2(-4), PN2(-4), N2(-4)	**NZM2-XTVDVR** 260180	1 off	
	NZM3(-4), PN3(-4), N3(-4)	**NZM3-XTVDVR** 260182	1 off	
	NZM4(-4), N4(-4)	**NZM4-XTVDVR** 266618	1 off	

Extension shaft



	For use with	Part no. Article no. when ordered separately	Std. pack	Note
400 mm max. mounting depth	NZM1(-4), PN 1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4)	**NZM 1/2-X V4** 261232	1 off	can be cut to required length.
	NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	**NZM 3/4-X V4** 261234	1 off	
600 mm max. mounting depth	NZM1(-4), PN 1(-4), N1(-4) NZM2(-4), PN2(-4), N2(-4)	**NZM1/2-XV6** 260191	1 off	
	NZM3(-4), PN3(-4), N3(-4) NZM4(-4), N4(-4)	**NZM3/4-XV6** 260193	1 off	

For maximum shaft length 60 mm **Part no.** Article no. when ordered separately	Std. pack	**Note**	Extremely narrow fittings **Part no.** Article no. when ordered separately	Std. pack	**Note**
NZM1-XTVD-60 271504	1 off	**Door interlock** • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)-60** • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/ designation label can be clipped on.	**NZM1 -XTVD-0** 279392	1 off	**Door interlock** • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)-0** • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/ designation label can be clipped on.
NZM2-XTVD-60 271505	1 off		**NZM2 -XTVD-0** 279393	1 off	
NZM3-XTVD-60 271506	1 off		**NZM3 -XTVD-0** 279394	1 off	
NZM4-XTVD-60 271507	1 off		**NZM4 -XTVD-0** 279395	1 off	
NZM1-XTVDV-60 271508	1 off		**NZM1-XTVDV-0** 279396	1 off	
NZM2-XTVDV-60 271509	1 off		**NZM2-XTVDV-0** 279397	1 off	
NZM3-XTVDV-60 271510	1 off		**NZM3-XTVDV-0** 279398	1 off	
NZM4-XTVDV-60 271511	1 off		**NZM4-XTVDV-0** 279399	1 off	
NZM1-XTVDVR-60 271512	1 off	**Door interlock** • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)-60** • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/ designation label can be clipped on.	**NZM1-XTVDVR-0** 279400	1 off	**Door interlock** • Can not be defeated in the locked OFF and ON positions • Can be modified such that it can be defeated from the outside using a screwdriver, when it is in the unlocked ON position. • Door can be opened in OFF **NZM…-XTVD(V)-0** • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/ designation label can be clipped on.
NZM2-XTVDVR-60 271513	1 off		**NZM2-XTVDVR-0** 279401	1 off	
NZM3-XTVDVR-60 271514	1 off		**NZM3-XTVDVR-0** 279402	1 off	
NZM4-XTVDVR-60 271515	1 off		**NZM4-XTVDVR-0** 279403	1 off	

Door coupling rotary handles for North America

Difference to normal IEC handles:
Door opening only possible with active rotation beyond the 0 position.

Door coupling rotary handles

Complete including rotary drive and coupling parts
Extension shaft additionally required.
Degree of protection IP66/UL/CSA type 4X,





	For use with	Part no. Article no. when ordered separately	Std. pack	Note
Standard, black/grey				
Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1, N(S)1	**NZM1-XTVDV-NA** 100683	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on.
	NZM2, N(S)2	**NZM2-XTVDV-NA** 100684	1 off	
	NZM3, N(S)3	**NZM3-XTVDV-NA** 100685	1 off	
	NZM4, N(S)4	**NZM4-XTVDV-NA** 100686	1 off	





Red-yellow for emergency witching off				
Lockable on handle and switch with up to 3 padlocks. Lockable in 0 position on handle. With door interlock. Lockable on switch in 0 position.	NZM1, N(S)1	**NZM1-XTVDVR-NA** 271449	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/ designation label can be clipped on.
	NZM2, N(S)2	**NZM2-XTVDVR-NA** 271450	1 off	
	NZM3, N(S)3	**NZM3-XTVDVR-NA** 271451	1 off	
	NZM4, N(S)4	**NZM4-XTVDVR-NA** 271452	1 off	



Extension shaft

	For use with	Part no. Article no. when ordered separately	Std. pack	Note
400 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4)	**NZM1/2-XV4** 261232	1 off	can be cut to required length.
	NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4)	**NZM3/4-XV4** 261234	1 off	
600 mm max. mounting depth	NZM1(-4), PN1(-4), N(S)1(-4) NZM2(-4), PN2(-4), N(S)2(-4)	**NZM1/2-XV6** 260191	1 off	
	NZM3(-4), PN3(-4), N(S)3(-4) NZM4(-4), N(S)4(-4)	**NZM3/4-XV6** 260193	1 off	

For maximum shaft length 60 mm **Part no.** Article no. when ordered separately	Std. pack	**Note**	Extremely narrow fittings **Part no.** Article no. when ordered separately	Std. pack	**Note**
NZM1-XTVDV-60-NA 100667	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. **NZM...-XTVDV-60-NA** • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on.	**NZM1-XTVDV-0-NA** 100675	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. Can be defeated from the outside using a screwdriver. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on.
NZM2-XTVDV-60-NA 100668	1 off		**NZM2-XTVDV-0-NA** 100676	1 off	
NZM3-XTVDV-60-NA 100669	1 off		**NZM3-XTVDV-0-NA** 100677	1 off	
NZM4-XTVDV-60-NA 100670	1 off		**NZM4-XTVDV-0-NA** 100678	1 off	
NZM1-XTVDVR-60-NA 100671	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. **NZM...-XTVDV-60-NA** • For maximum shaft length 60 mm • Without shaft support • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on.	**NZM1-XTVDVR-0-NA** 100679	1 off	**Door interlock** • Can not be defeated in the locked OFF position. • Door opening possible with active rotation beyond the 0 position. • Cannot be combined with mechanical interlock • External warning plate/designation label can be clipped on. **NZM...-XTVDVR-0-NA** • For extremely narrow fittings • With special short extension shaft • Cannot be combined with additional handle NZM...-XDZ • External warning plate/designation label can be clipped on.
NZM2-XTVDVR-60-NA 100672	1 off		**NZM2-XTVDVR-0-NA** 100680	1 off	
NZM3-XTVDVR-60-NA 100673	1 off		**NZM3-XTVDVR-0-NA** 100681	1 off	
NZM4-XTVDVR-60-NA 100674	1 off		**NZM4-XTVDVR-0-NA** 100682	1 off	