



# Straight Blade Plugs & Connectors Miscellaneous Configurations

**IP20**  
 Suitability




**5333-DF**




**5741-AN**



**3867**



**7251-DF**



**8302-AN**

Catalog Number	Rating		Description	Cord Diameter	NEMA Config. No.	3rd Party Compliance		
	A.	V.				UL	FSUL	CS
<b>3-Pole 4-Wire Grounded</b>								
5333-DF	20	125/250	Plug, Yellow	.350"-1.062"	14-20P	•		•
5746-AN	30	125/250	Angle Plug, Yellow		14-30P	•		
5741-AN	30	3Ø, 250	Angle Plug, Yellow		15-30P	•		•
5745-AN	50	125/250	Angle Plug, Yellow		14-50P			
5751-AN	50	3Ø, 250	Angle Plug, Yellow		15-50P	•		•
5761-AN	60	3Ø, 250	Angle Plug, Yellow		15-60P	•		•
3867	30/50	125/250	Angle Plug, Yellow		14-30P/14-50P	•		•
<b>4-Pole 4-Wire Ungrounded</b>								
7251-DF	20	3ØY, 120/208	Plug, Yellow	.365"-.775"	18-20P	•		•
8302-AN	60	3ØY, 120/208	Angle Plug, Yellow		18-60P			



NEMA 14-20P



NEMA 14-30P



NEMA 15-30P



NEMA 14-50P



NEMA 15-50P



NEMA 15-60P



NEMA 18-20P



NEMA 18-60P

All devices listed on this page conform to NEMA WD-1.