

## PAT46LWS

### 15-Ton, Light Weight C-Head Hydraulic Self-Contained, 18V Lithium-Ion

- 2" jaw opening
- Used with P dies; U dies with PUADP1 adapter (sold separately)
- Light weight, scoop style C-head with 355° head rotation
- Overmolded, ergonomic handle
- Improved ergonomic balance
- Includes 2 batteries, charger, and polymer carrying case
- **EP Enhanced Power** labeled tools accept 2.0, 3.0, 4.0, and 5.0Ah Makita batteries

#### For Use On:

##### Copper - #8 AWG Str. - 1500 kcmil

Code Cable, Navy Cable, Flexible, Extra Flexible  
1/2" - 1" Ground Rods

##### Terminals, grounding:

to 500 kcmil; YGA, YGHA, YGF

##### Terminals, uninsulated:

#8 - 1500 kcmil; YA, YA-2N, YA-L, YA-LB, YA-TC,  
YA-2LN, YAB-4N, YAV-L, YAV-RS, YA-TC-FX

##### Terminals, insulated:

#8 - 2/0; YAEV-L, YAEV-H, YAEV-RS, YAEV-RH

##### Splices:

#8 - 1500 kcmil; YS, YS-T, YS-L, YS-LB, YST,  
YSP-T, YGS, YGHS

##### Taps:

#14 - 1000 kcmil; YH, YCHC  
to 4/0 AWG; YC-C

##### Taps, grounding:

to 500 kcmil; YGHC-C, YGHP-C, YGHR-C

##### Aluminum - #8 AWG - 1250 kcmil

Code Cables

##### Terminals: YA-A, AYP, AYPO

##### Splices: YS-A, YS-AT, YRB

##### Taps: YFD, YFN, YFO, YFR

**ACSR** - see Overhead Transmission & Distribution  
Sections H & I of the current BURNDY® Master  
Catalog



#### Specifications:

<b>Output Force:</b>	15 Tons
<b>Tool Weight:</b>	18.9 lbs
<b>Size:</b>	18.00" x 14.00" x 3.00"
<b>Die Style:</b>	P and U style (with PUADP1)
<b>Jaw Opening:</b>	2.00"
<b>Operating Voltage:</b>	18 V-DC Lithium-Ion
<b>Recharge Time:</b>	30 minutes (3.0Ah) 45 minutes (5.0Ah)
<b>Warranty:</b>	5 year limited warranty Lifetime warranty on INFINITY DRIVE® 3 year on batteries and charger

#### Accessories:

<b>Catalog Number:</b>	<b>Description:</b>
P15K:	Cutter Die, max. diameter 1.2"
PUADP1:	U Die Adapter
BAT18VLI:	3.0Ah Li-Ion battery
BAT18V5AHLI:	5.0Ah Li-Ion battery
PATCHGRLI:	120V-AC Charger
PATCHGRLIDC:	12/24V-DC Charger
PT208620:	Lanyard

#### Variations: (additional variations may be available)

<b>Catalog Number:</b>	<b>Description:</b>
PAT46LWSLI	with 3.0Ah Li-Ion batteries
PAT46CLWSLI	with rubber covered head (3.0Ah)
PAT46LWSL5	with 5.0Ah Li-Ion batteries
PAT46CLWSL5	with rubber covered head (5.0Ah)

See Important Notes on Page N-6.