CLEARCHOICE **CLEAR CHOICE**

REDUCE YOUR CLEAR**TAP**® **INVENTORY** AND LOWER CLEAR SPLICE. **INSTALLATION COSTS** 811

1560

CLEAR CHOICE

THE CLEARCHOICE™ SOLUTION ANOTHER FIRST ... FROM **ILSCO**.

First, ILSCO introduced ClearTap®, an innovative multi-tap connector with a transparent insulating cover. Contractors loved it then, and depend on it today.

Now, with the addition of more ClearTap sizes — and the introduction of RocketSplice $^{\mathbb{M}}$, a ClearSplice $^{\mathbb{M}}$ Connector — we proudly present the expanded family of ILSCO ClearChoice connectors.

ILSCO is The ClearChoice Solution ... and the reasons are obvious.

No other line of connectors delivers more versatility than The ClearChoice Solution. ILSCO ClearTap connectors — now available in both smaller and larger sizes — give you dozens of ways to solve any multi-tap connector challenge.

RocketSplice, like ClearTap, features a transparent, insulating cover that allows easy visual inspection of your splice, and the sleek design is perfect for working in confined spaces. All ClearChoice products are dual rated for copper and/or aluminum conductors and are UL Listed and CSA Certified.

AN EXCLUSIVE COMBINATION OF LABOR-SAVING FEATURES

ClearTap and RocketSplice require less labor due to the elimination of tape and covers required with traditional wiring methods such as split bolts and other labor-intensive connector designs.

With ClearChoice there is no taping, no lost caps, just tap and tighten. Every ClearTap connector offers dual entry from both sides, and has unique, self-closing openings that automatically hold wires in place. The transparent cover makes inspection a breeze.

MORE APPLICATIONS WITH LESS INVENTORY


While some companies boast about the quantities of variations in their offering, ILSCO lets you complete virtually any job with a selection of just thirty (30) versatile connectors, not hundreds.

ClearTap covers the complete range from #14 AWG to 800 MCM in just twenty-three (23) sizes and new RocketSplice offers a conductor range from #14 AWG to 500 MCM in only seven (7) sizes. That means less inventory and increased inventory turns for the distributor and easier selection for the contractor.



CLEARCHOICE

MORE APPLICATIONS WITH LESS INVENTORY





Type DCT	CITADTAD®	INICHIATED	MUITI-TAP CONNECT	\sim D

	Catalog	Number Design	1.0-1.0	No. Of Ports	Wire Range AL or CU	Dimensions (in.)			Hex
	Number					Length	Width	Height	Size
	PCT-2-4	••	1	2	4-14	1.46	1.63	1.61	slotted
	PCT-4-4	● ● ●	1	4	4-14	2.46	1.63	1.61	slotted
	PCT-6-4		1	6	4-14	3.46	1.63	1.61	slotted
	PCT-8-4		1	8	4-14	4.46	1.63	1.61	slotted
	PCT-2-2/0	●●	2	2	2/0-14	2.61	2.30	1.97	3/16
	PCT-4-2/0	\odot	2	4	2/0-14	4.30	2.30	1.97	3/16
	PCT-6-2/0	00000	2	6	2/0-14	5.98	2.30	1.97	3/16
	PCT-8-2/0	0000000	2	8	2/0-14	7.67	2.30	1.97	3/16
	PCT-2-4/0	<u></u>	2	2	4/0-6	2.75	2.49	2.25	5/16
	PCT-4-4/0	$\bullet \bullet \bullet \bullet$	2	4	4/0-6	4.61	2.49	2.25	5/16
-	PCT-6-4/0	00000	2	6	4/0-6	6.47	2.49	2.25	5/16
	PCT-8-4/0		2	8	4/0-6	8.33	2.49	2.25	5/16
	PCT-2-350	●●	2	2	350MCM-6	3.31	2.69	2.65	5/16
	PCT-4-350	9 9 9 9	2	4	350MCM-6	5.62	2.69	2.65	5/16
	PCT-6-350		2	6	350MCM-6	7.93	2.69	2.65	5/16
	PCT-8-350		2	8	350MCM-6	10.24	2.69	2.65	5/16
	PCT-2-600	●●	2	2	600MCM-4	3.90	3.43	3.27	1/2
	PCT-4-600	lacktriangledown	2	4	600MCM-4	6.64	3.43	3.27	1/2
	PCT-6-600		2	6	600MCM-4	9.39	3.43	3.27	1/2
	PCT-8-600		2	8	600MCM-4	12.14	3.43	3.27	1/2
	PCT-2-800	••	2	2	800MCM-250MCM	4.25	3.43	3.40	1/2
	PCT-4-800	lacktriangledown	2	4	800MCM-250MCM	7.40	3.43	3.40	1/2
	PCT-6-800	00000	2	6	800MCM-250MCM	10.50	3.43	3.40	1/2

UL Listed 486B. Not suitable for direct burial.









TYPE SPAR ROCKETSPLICE™ INSULATED SPLICER-REDUCER CONNECTOR

Catalog	Connector	Wire Range	Dimensions (in.)			Hex
Number	Design		Length	Width	Height	Size
SPAR-4		4-14	3.30	1.55	.90	slotted
SPAR-2		2-14	3.83	1.75	.95	slotted
SPAR-1/0		1/0-14	4.80	1.94	1.14	slotted
SPAR-4/0		4/0-6	5.67	2.43	1.50	5/16
SPAR-250		250MCM-6	7.91	2.43	1.62	5/16
SPAR-350		350MCM-6	7.91	2.43	1.62	5/16
SPAR-500		500MCM-3/0	8.86	3.23	2.04	3/8

UL Listed 486B. Not suitable for direct burial.



ILSCO • 4730 Madison Road, Cincinnati, Ohio 45227, U.S.A. • Phone: (800) 776-9775, (513) 533-6200 Fax: (513) 871-4084 • E-mail: sales@ilsco.com, Web site: http://www.ilsco.com

